

# S-202 SDT Adhesive for Static Dissipative Tile



**CAUTION**

S-202

**EYE AND SKIN IRRITANT**

## STIR WELL BEFORE USING.

For use with the following Installation

System:

- Static Dissipative Tile (SDT)

## DESCRIPTION:

<b>Type:</b>	Water-based resin
<b>Color:</b>	Black
<b>Taggants:</b>	None
<b>Trowel:</b>	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel with S-894 Fine Notch Blade Fine notch (1/32" deep, 1/16" wide, 5/64" apart), U-notch
<b>Coverage:</b>	Approximately 150 sq. ft./gal. (14 sq. m)
<b>Units:</b>	1 gallon (3.78 L) and 4 gallons (15.14 L)
<b>Shelf Life:</b>	12 months, unopened
<b>Freeze/Thaw Stable:</b>	No, keep from freezing
<b>VOC Content:</b>	< 50 g/L; calculated and reported, SCAQMD 1168
<b>Open Time:</b>	Until dry to touch, 60 minutes or more
<b>Working Time:</b>	Up to 6 hours (May vary based on job conditions, substrates, temperature, and humidity)
<b>Clean Up:</b>	Wet or Dry — clean, white cloth and mineral spirits
<b>Subfloors:</b>	All grade levels of concrete and suspended wood Ceramic, terrazzo, polymeric poured and certain metal subfloors when properly prepared with S-194 Radiant Heated subfloors where the surface temperature does not exceed 85° F (29° C)
<b>Advantages:</b>	Moisture and alkali resistant Long working time (up to 6 hours)