

S-288 Flooring Adhesive



CAUTION

S-288 **EYE AND SKIN IRRITANT**

STIR WELL BEFORE USING.

For use with the following Installation Systems:

- Fiberglass-Reinforced Sheet Flooring
- ToughGuard II
- Alterna
- Residential LVT Planks
- Rigid Core Planks
- Commercial Luxury Vinyl Tile Flooring

DESCRIPTION:

Type:	Water-based rubber resin
Color:	Creamy beige
Taggants:	Yes — green glitter
Trowel:	S-891 Notched Steel Trowel or S-892 Replaceable Blade Trowel; Fine notch — (1/32" deep, 1/16" wide, 5/64" apart), U-notch For Natural Creations® with Diamond 10® Technology 1/32" deep, 1/16" wide, 1/32" apart, U-notch
Coverage:	Fine notch: 220-260 sq. ft./gallon (20.4-24.2 m) U-notch: 250-300 sq. ft./gallon (23-28 sq. m)
Units:	1 gallon (3.78 L) and 4 gallons (15.14 L)
Open Time:	Porous substrates — Set-in-wet: Minimum 10-20 minutes Nonporous substrates — Dry-to-touch: 30 minutes or more
Working Time:	Up to 1 hour (May vary based on job conditions, substrates, temperature, and humidity)
Shelf Life:	2 years, unopened
Freeze/Thaw Stable:	Yes, to 10° F (-12° C)
VOC Content:	< 14 g/L; calculated and reported, SCAQMD 1168
Clean Up:	Wet — clean, white cloth with neutral detergent and water Dry — clean, white cloth and mineral spirits
Subfloors:	All grade levels of concrete, existing resilient floors, ceramic, terrazzo, marble, steel, stainless steel, aluminum, polymeric poured floors and suspended wood
Advantages:	For Full Spread Installation Systems Moisture and alkali resistant Strong, early grab Armstrong Flooring Guaranteed Installation System (AGIS) Guarantee included as part of Armstrong Flooring Installation System when installing Armstrong® vinyl-back sheet flooring and residential Luxury Vinyl Tile Nonflammable, ammonia-free & low odor; contains low or no organic solvents Contains no reportable hazardous substance (per current regulations)