NEUTRAL CLEANER

Hilway Direct

Items HD-NC1L, HD-NC133

Instructions for Use:

Cleaning After Installation Directions:

- 1. Following flooring manufacturer instructions for wait time before first cleaning a newly installed floor.
- 2. Sweep, or vacuum on hard floor setting, to remove loose dirt and soil from floor.
- 3. For stubborn dirt, dilute Hilway Direct Neutral Cleaner 1:10. Reduce concentration accordingly for slightly soiled floors.
- 4. Distribute cleaning solution over floor and allow to stand for 10-20 minutes then agitate the flooring surface with a red scrub pad or appropriate scrub brush on an automatic scrubber or manually. Do not allow solution to dry on floor.
- 5. Pick up dirty solution with wet-dry vacuum or trail mop.
- 6. Rinse floor thoroughly.
- 7. Allow floor to air dry.

Dilution Rate: 1:10 = 1-1/2 C per 1gal water; 13oz per gallon of water; 1L to 2.67 gallons water

Routine/Daily Cleaning Directions:

- 1. Sweep, or vacuum on hard floor setting, to remove loose dirt and soil from floor.
- 2. Dilute Hilway Direct Neutral Cleaner 1:200 (3/4 oz cleaner to 1 gallon water) for Mop & Bucket or 1:400 (1/3 oz cleaner to 1 gallon water) for Automatic Scrubber. Adjust to stronger dilution for very dirty floors.
- 3. For mopping, use a 2-bucket system. Mop floor with diluted cleaning solution then rinse mop head in clean rinse water and wring well before dipping back into cleaning solution.
- 4. Trail mop excess soil and wet areas with a clean, tightly wrung out mop.
- 5. For best results on very dirty floors, rinse floor after cleaning by mopping with clean water however rinsing floor is not required.
- 6. Allow floor to dry completely.

Option: Spray & wipe cleaning- Dilute cleaner in a spray bottle at 1:200 dilution ratio. Spray small area of floor, wipe with flat mop, cotton or microfiber pad. Repeat until floor is completely cleaned. Change mop pad when it becomes dirty. Wash mop pad after use.

Dilution Rates: 1:200 = 1 tsp per 32oz water; 1-1/2 Tbsp per 1gal water \ 1:400 = 1/2 Tbsp per 1gal water

For Use On

Vinyl/Luxury sheet-plank-tile (LVT/LVP), VCT, PVC, Non-PVC, Rubber, Linoleum, Cork, Asphalt Tile, Marble, Slate, Concrete, Quarry Tile, Terrazzo. Safe for use on all floor types.

Caution

Eye irritant. Avoid contact with skin and eyes. Do not taste or swallow. In case of contact with eyes or skin flush with plenty of water. If irritation develops, seek medical attention. In case of ingestion, flush mouth with water, drink large quantities of water and seek immediate medical attention, DO NOT induce vomiting. KEEP OUT OF REACH OF CHILDREN.

Additional Instructions

- A wet floor is slippery. Use caution signage to prevent traffic on floor while it is wet. Read full SDS (available for download: www.hilway.com) and product label prior to use.
- 2-Bucket system: 1 bucket for cleaning solution and a 2nd bucket for clean water to rinse mop head.
- Mops: Change mop head/pad when too dirty to clean effectively. Wash mop heads/pads after use. Most are machine washable.

Handling and Storage

Freeze-thaw stable however recommended storage is at: 68°F (20°C). Do not store near food. Shelf life is approximately 2 years.

Coverage

- 33.8 Ounces: up to 10,000 square feet depending on dilution ratio
- 1.33 Gallon: up to 52,000 square feet depending on dilution ratio