

TECHNICAL INFORMATION

ParkettSoap R2U



ParkettSoap R2U is a ready to use cleaning solution for the deep cleaning of wood surfaces which are treated with oxidizing oils.

- Ready to use, no mixing required
- Removes grey and faded layers after exposure to sunlight
- Great for indoor and outdoor use
- Water-based yet powerful formula to remove residue and dirt

Recommended use:

For wood surfaces which are treated with oxidizing oils indoors (floors etc.) and outdoors (decks etc.)

Technical Data

Art.-no.
10060

Item-#:
LO-MA-010



1 Gal.



4



200

pH

10.0

Contents

< 5% soap, METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE

Storage and transportation

Shelf life: 36 months in unopened containers. Store and transport between 40°F to 80°F (5°C to 25°C). KEEP FROM FREEZING.

Application

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- Shake material well before use.

Application Tool

LOBATOOL wiper mop, Single disc machine, LOBASAND SpecialPad green

Coverage

1,000 square feet / 1 gal container.

13/12/2019



TECHNICAL INFORMATION

ParkettSoap R2U



Application

Intensive cleaning:

- Pour ParkettSoap R2U undiluted onto the floor and distribute it with a mop.
- Buff the wet floor with a LOBA SpecialPad green to dissolve dirt and soil.
- Take off the diluted remains of ParkettSoap R2U with a clean mop or a water vacuum.
- Then wipe the floor with clear water.
- After drying, the floor must be treated with an impregnation oil like 2K ImpactOil or Deck & Teak Oil.

General guidelines

Cleaning of tools: Clean tools and equipment with water.

Side bonding: Parquet that has not been shear-resistantly bonded in place, wood planks, wooden pavings, industrial parquet and parquet on underfloor heating as well as types of wood with a short moisture changing times (e.g. beech) show dimensional changes caused by quickly varying climate (rel. air humidity, temperature). When applying oil side bonding and thus unregular cracks in joints can not appear.

Safety Precautions: Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

First Aid: If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

13/12/2019

