

# TECHNICAL INFORMATION

## NatureOil



Water-based maintenance oil. To protect finished oiled floors.

- Ready-to-use, solvent-free and soap-free
- Reliably retains the matt finish of oiled hardwood floors
- Ideal for treating the whole floor or touching up smaller areas
- Simple application with cloth or sponge

### Recommended use:

For oiled wood floors. For the initial treatment of hand-oiled wood floors, as well as for wood floors that have been factory pre-treated with oxidizing oils, if the use of maintenance oils is approved by the manufacturer. Not suitable for use on non-absorbent surfaces.

## Technical Data

### Art.-no.

10100

### Item-#:

LO-FI-115



1 Qt.



15

### Contents

water, anionic surfactants, perfume oil, preservatives, cobalt-free siccatives

### Storage and transportation

Shelf life: 24 months in unopened containers. Store and transport between 40°F to 80°F (5°C to 25°C). KEEP FROM FREEZING.

## Application

- BEFORE USING, READ AND UNDERSTAND ALL LABEL INSTRUCTIONS AND MATERIAL SAFETY DATA SHEETS.
- For technical advice call our LOBA-WAKOL Technical Service at 1-800.230.6456.
- ALWAYS PREPARE A SAMPLE OR TEST AREA TO DETERMINE COMPATIBILITY, APPEARANCE AND DESIRED RESULTS.
- Shake material well before use.
- Do not thin. Do not add water.
- Do not apply at temperatures below 55°F. Make sure material is at room temperature. Always maintain adequate ventilation during all phases of the coating and drying process.
- Apply evenly at the recommended coverage rate. Avoid streaks and puddles and lap marks.

### Application Tool

Lint free cotton cloth

13/12/2019



## Application

---

### Coverage

350 -1,000 square feet per 1 quart bottle.  
Depending on absorbency of the wood.

### Drying time

- Slightly stressable after 4-6 hours.
- Fully stressable after 12 hours.

### Maintenance Process

For newly installed multi-layer flooring elements,  
as well as freshly oiled floors, clean the floor thoroughly to remove all dust and grit (sweeping, vacuuming) and apply an even coat of Oil using a lint-free cloth or a sponge, wiping off any excess oil; do not allow the oil to pool or puddle.

For existing floors with moderate wear.

clean thoroughly with LOBA Hardwood FloorCleaner, if necessary prepare the surface using a floor machine fitted with mildly abrasive pads (beige/green). Allow floor to dry completely. Apply Oil.

Floors with more extensive damage

may require treatment with impregnation oil. For more information about such treatment, see the LOBA floor-care instructions for oiled hardwood floors.

For larger areas

the product can be applied using the SprayCleaner method. Spray Oil onto the floor, and buff the entire area using a floor machine fitted with a white pad.

On non-absorbent surfaces,

e.g. newly installed or hardly used parquet and hardwood flooring that was factory finished with UV oil, poor wetting may result. A suitable maintenance product for such flooring is NatureWax.

### Compatibility

When this product is used in combination with other LOBA products the Technical Information of these products have to be followed. Always prepare test areas to determine suitability of other products than LOBA.

### Important information

#### **WARNING! SELF-IGNITION:**

**Store cloth, pads and other tools contaminated with oil in closed metal container or soak in water immediately after use. Do not leave used rags on jobsite! Do not dispose of with sawdust!**



## General guidelines

---

**Cleaning of tools:** Clean tools with solvents such as brush cleaner.

**Cure Time:** The stated drying and cure times are based on ideal conditions (68°F, 50% rH) at the recommended application rates. Recommended conditions are 50°F-80°F/40-65%rH). Insufficient ventilation, high humidity, lower temperatures can prolong the curing process considerably. Do not use safety covers on floor, do not replace carpets or rugs and also do not clean floors with a damp cloth before the final curing has been reached. Remaining excessive material will prolong curing. On some exotic woods curing time can be extended.

**Safety Precautions:** Even when working with low or zero-emission products the usual safety measures must be taken. Keep away from children. Do not eat, drink or smoke in working areas. Wear suitable safety gloves. Clean left-overs off of hands. Change soiled clothes.

**First Aid:** If swallowed, do not induce vomiting. Call for medical help immediately. Never give anything by mouth to an unconscious person. If breathing is difficult or other respiratory complaints, remove to fresh air and get medical attention. In case of eye contact, immediately flush eyes for several minutes under running water. Generally this product does not cause skin irritation. Call a physician if irritation occurs.

**Special Information** The information in this document and any other information or advice we provide is intended for our customers only, and all information and advice is subject to the terms and limitations in Loba-Wakol's General Terms and Conditions, including without limit its limited warranty ("Terms"). The Terms are not expanded, changed or waived by the information in this document or by any information or advice given by Loba-Wakol. Loba-Wakol has no relationship or obligation to anyone other than the customer that originally purchases the product from Loba-Wakol.

The information in this document and any other information or advice we provide is the result of our prior experience and our knowledge of our products. Due to the wide variety of application possibilities and processing conditions, it is the customer's responsibility to test our product for suitability for its intended purpose. When in doubt, call our Technical Service for support. Technical Information is also available by visiting our website [www.loba-wakol.com](http://www.loba-wakol.com). You must read and understand, and have your professional installer read and understand, all information contained in our Terms and in our published specifications, technical data sheets, written directions for installation, use and maintenance, and labels on the product. If you have any questions during application or use, immediately stop the application and use and contact our Technical Service. For information about other products offered by Loba-Wakol, please check the technical information concerning those products.

The words or symbols denoted by ® stand for trademark rights that are at least registered and protected in the territory of Germany.

