

Antique Oak Lye produces an ammonia smoked appearance to oak wood. This product is user-friendly but corrosive and should be handled with caution during application. Since the product reacts with the tannic acid in the oak, the colour after application may vary depending on the concentration of tannin in the wood. It creates a very unique color and Vintage appearance. The final color achieved after 1-2 months.

- **Requires subsequent treatment with oil or soap**
- **Only for oak wood**
- **Does not contain pigments**



AppArea

Used for priming of oak wood. Creates an ammonia-smoked look.

Work_Descrip_Label

Preparation_Label	The unfinished woodwork must be clean, dry and finely sanded (grit 100-120) before applying the lye. Always remember to test on a less visible spot to check the compatibility of the surface with the product.
Treatment	Shake the container well and pour the lye into a plastic bucket. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 litre of lye to 110 sq.ft. of wood. Leave lye primed wood to dry for approx. 2-4 hours at 68°F. Clean with WOCA Intensive Wood Cleaner and leave to dry for approx. 8-12 hours at 68°F. De-nib standing fibres with a medium e.g. green or maroon, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil or soap.
NoteTxt	Depending on the amount of moisture and tannin in the oak, the color may vary. Sapwood does not change to a dark color.

DryingTime

DryingTime	2-4 hours.
------------	------------



Techdata_label

Declaration	Sodium hydroxide, water.
Density	1-1.08
PHVvalue	13-14
ShelfLife	36M
Consumption	85-110 sq. ft./L
Colours	Clear.
CleaningTools	Water.
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
AvailPotSizes	84.54 fl.oz.
Authorisations	IBR-certified

MaintenanceProd

RelatedProducts	Intensive Wood Cleaner, #551525US
ApplicationTool	WOCA Applicator, a nylon brush or roller Plastic bucket

Contact_Label

WOCA Denmark A/S
Tvæervej 6
DK - 6640 Lunderskov
T +45 9958 5600
info@wocadenmark.com
wocadenmark.com

Disclaimer_Long