



Wood Lye  
**Minimizes yellowing of hardwood**

Technical\_Data\_Sheet\_Label

19.10.2020 - p. 1/2

Wood Lye is used for priming of unfinished or newly sanded interior woodwork i.e. floor, stairs, furniture and panels. The priming minimizes the wood from yellowing and enhances the wood grain, creating a colored wash effect, depending on the chosen color. Wood Lye may be used on all types of wood.

- **For a lighter finish**
- **Reduces yellowing process of the wood**
- **Requires subsequent treatment with oil, lacquer or soap**
- **Suitable for any type of wood**



## AppArea

Used for priming of unfinished and newly sanded interior wood. Ideal for all types of wood.

## Work\_Descrip\_Label

Preparation_Label	<p>The unfinished woodwork must be clean, dry and finely sanded [grit 100-120] before applying the lye.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well and pour the lye into a plastic bucket. It is important that no pigments are left in the container. Stir regularly during the application to prevent the pigments from settling to the bottom. Apply an even coat of the lye with the WOCA Applicator, a nylon brush or roller lengthwise along the grain. Apply at least 1 L of lye per 110 sq. ft. of wood. Leave wood to dry for approx. 8-12 hours at 68°F. De-nib standing fibres and remove excess pigments with a medium e.g. green or maroon, sanding polishing pad. Remove the sanding dust with a vacuum cleaner. Finish the wood surface with a WOCA oil, water based finish or soap.</p>

## DryingTime

DryingTime	8-12 hours.
------------	-------------



Wood Lye  
**Minimizes yellowing of hardwood**

Technical\_Data\_Sheet\_Label  
19.10.2020 - p. 2/2

## Techdata\_label

Declaration	Sodium hydroxide, water, white pigments, <5% non-ionic surfactants, <1% preservative.
Density	1 g/cm <sup>3</sup> .
PHVvalue	9-10.
ShelfLife	36M
Consumption	85-110 sq.ft/L.
Colours	White and Grey.
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
VOCTxt	VOC-Max: 0 g/l.
AvailPotSizes	84.54 fl.oz. [2.5 L].
Migration_Test	EN 71-3.
Authorisations	IBR-certified.

## MaintenanceProd

ApplicationTool	WOCA Applicator, a nylon brush or roller Plastic bucket.
-----------------	---

## Contact\_Label

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
[info@wocadenmark.com](mailto:info@wocadenmark.com)  
[wocadenmark.com](http://wocadenmark.com)

*Disclaimer\_Long*