



Use Maintenance Oil Diamond Active for the ultimate care and maintenance of your oiled wood floor. This exclusive, low-odour, extremely tough maintenance oil is made from the absolute highest quality raw materials, to benefit both you and your oiled floor. In addition to being very easy to use and assuring minimal product waste, the maintenance oil refreshes the natural, warm glow of the wood and increases resistance to stains, via a unique hyper cross linking technology. Maintenance Oil Diamond Active is suitable for both manual and machine application to oiled floors.

- **Resistant to liquids such as water, coffee, tea and red wine**
- **Resistant to scratches and marks**
- **Gives the wood a beautiful, breathable surface**
- **IBR-certified**



## AppArea

For oiled surfaces.

## Work\_Descrip\_Label

Preparation_Label	<p>Product, room and floor temperature should be 59-86°F. Make sure that the room is well-ventilated for optimal evaporation and drying time. Wash the floor with WOCA Intensive Wood Cleaner and leave the floor to dry for at least 8 hours before application of the maintenance oil.</p> <p>Always remember to test on a less visible spot to check the compatibility of the surface with the product.</p>
Treatment	<p>Shake the container well. Apply approx. 3 fl. oz. of Maintenance Oil Diamond Active per 45 sq. ft. floor using a pad, short-bristled paint roller (1/4") or a buffing machine with a white pad on slightly larger areas. Make sure that the oil is polished well into the wood. Continue polishing until the wood seems saturated and the surface has an even, uniform appearance. Remove excess oil with clean, lint-free cotton cloths, before proceeding to the next section. The surface should not appear wet and no excess oil should remain on the surface. Continue, following the aforementioned method, until the whole floor has been treated.</p>
NoteTxt	<p>Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.</p>

## DryingTime

DryingTime	24 hours at 68°F.
DryMachinePolis	4 hours at 68°F.
DryManualPolish	24 hours at 68°F.
FullyHard	3 days.
Rec	Do not expose the floor to water or clean it for the first 3 days, while the oil is hardening.



Maintenance Oil Diamond Active  
**Revitalises oil-treated wood**

Technical\_Data\_Sheet\_Label

19.10.2020 - p. 2/2

## Techdata\_label

Declaration	Drying oils.
ShelfLife	36M
AppTemp	+59-86°F.
Consumption	430-540 sq.ft./L.
Colours	Natural and White
CleaningTools	WOCA Solvent or turpentine.
Storage	+50-77°F. Keep out of reach of children. Do not expose to heat (e.g. sunlight). Store frost-free during winter and cool during summer (max. +77°F).
VOCTxt	VOC-Max: 20 g/l.
AvailPotSizes	84.54 fl. oz.
Migration_Test	EN 71-3:2013
Authorisations	Danish Indoor Climate Labelling IBR: TVOC28/A+, AgBB Z-157.10-198

## MaintenanceProd

WeeklyCleanProd	Natural Soap
MonthlyCareProd	Oil Refreshing Soap
ReOilingProduct	Diamond Oil Active
RelatedProducts	Intensive Wood Cleaner
ApplicationTool	Pad, short-bristled paint roller or a buffing machine. Lint-free cloths.

## Contact\_Label

WOCA Denmark A/S  
Tvæervej 6  
DK - 6640 Lunderskov  
T +45 9958 5600  
[info@wocadenmark.com](mailto:info@wocadenmark.com)  
[wocadenmark.com](http://wocadenmark.com)

*Disclaimer\_Long*