

Technical_Data_Sheet_Label 19.10.2020 - p. 1/2

Maintenance Gel is for the care and maintenance of oiled indoor wood surfaces and floors. The oil is quick-drying and leaves an attractive, water and dirt-repellent surface. Maintenance Gel is suitable for furniture, kitchen work surfaces, floors and other indoor wooden surfaces. It can also be used for improved results on factory-oiled/UV-oiled surfaces.



- Especially suitable for UV-oiled surfaces
- Excellent results on factory-oiled surfaces
- Makes surfaces even more durable
- Can be applied manually with a polish pad and by machine using a buffer

AppArea

For care and maintenance of all oiled wood types. Only for indoor use.

Work_Descrip_Label

Preparation_Label

It is important that both wood and oil are at a temperature of at least 15°C, and ideally about 20°C, and that air humidity is approx. 50 %. Make sure that the room is well-ventilated, for optimal evaporation and drying time. Thoroughly clean the surface with WOCA Intensive Wood Cleaner. Sand the surface with grit 180 and vacuum clean the surface thoroughly.

Always remember to test on a less visible spot to check the compatibility of the surface with the product.

Treatment

Apply an appropriate amount of gel to a red/white WOCA Hand Scrubber and distribute over the surface in a thin, even coat. Continue polishing until the wood seems saturated. It is recommended to work on small areas at a time, as the gel is quick-drying. For larger areas, it would be advantageous to use a polishing machine. Remove excess gel with dry, lint-free cotton cloths or pads until the surface no longer appears wet. If the wood does not seem fully saturated after 4-6 hours, repolish with less gel than the first treatment, but follow the same procedure. Wait 4-6 hours before using the surface. Avoid getting water or dirt on the wood surface for the next 2-3 days.

DryingTime

DryLightUse 4-6 hours

FullyHard 2-3 days.

Rec The oiled surface should not be exposed to water for the first 2-3 days, as this can cause stains and

discoloration. Wood humidity must not exceed 18%. High temperature and low air humidity will shorten

drying times. Low temperature and high air humidity will extend drying times.

Techdata_label

Density 0.91 to 0.93 g/cm³.

ShelfLife 36M

AppTemp + 59-86°F.

Consumption 215-325 sq.ft/200 ml.

Colours Natural

CleaningTools Clean in turpentine.

Storage +50-77°F. Keep out of reach of children. Do not expose to

heat (e.g. sunlight). Store frost-free during winter and cool

during summer (max. +77°F).

VOCTxt VOC-Max: 125 g/l.

AvailPotSizes 6.76 fl.oz. (200 ml)

MaintenanceProd

WeeklyCleanProd Natural soap, #511025US

Natural soap Spray, #510900US

MonthlyCareProd Oil Refreshing Soap, #511225US

RelatedProducts Intensive Wood Cleaner, #551525US

ApplicationTool Hand Scrubber Flex Kit, Red, #599750

Hand Scrubber Flex Kit, White, #599752

Polishing cloth, grey, #596057

Contact_Label

WOCA Denmark A/S

Tværvej 6

DK - 6640 Lunderskov T +45 9958 5600

info@wocadenmark.com wocadenmark.com

Disclaimer_Long