



XL 25

GLOSS FLOOR FINISH

Metal Cross Linked with 25% Solids

**Non-Slip Fast Drying
Premium Floor Finish**

INFUSED WITH
INTERSEPT®
ANTIMICROBIAL



Tech Data Sheet

Depth and Clarity describes **XL 25 Gloss Floor Finish**. No need to burnish, but can be, XL 25 is a cross metal interlinked pure acrylic finish, built with advanced polymers providing a durable protection without creating unwanted build-up. Infused with **Intersept®** (an EPA reg anti-microbial) makes this and the entire line of XL finishes completely unique to the industry.

WHERE TO USE

XL 25 Gloss Floor Finish offers a variety of surface applications including VCT, Linoleum, Terrazzo, Rubber, Asbestos Tile, Asphalt Tile, Concrete, Sealed Wood and other resilient floors. Non-resilient floors such as Marble may require testing for adhesion.

DIRECTIONS

PREPARATION: Seal off areas to be stripped or finished. Floors may be very slippery until dry. Prior to application, floors should be completely stripped of old finish and neutralized. Floors should be completely dry before applying first coat and all subsequent coats. Do not use an air mover or fan to dry finish.

INTERSEPT® ANTIMICROBIAL

Intersept® is an antimicrobial preservative that protects the cured floor finish against a broad spectrum of bacteria and fungi, including odor - and stain-causing microorganisms.


Intersept® is registered with the EPA and meets stringent certification standards set by the three most recognized testing protocols related to indoor environmental quality – the State of Washington Protocol, CRI Green Label and GSA Antimicrobial Certification. Yet, despite its proven ability as a microbial inhibiting preservative, **Intersept®** is low in toxicity and contains no arsenic, heavy metals, phenols or formaldehyde.

TECHNICAL SPECIFICATIONS

COLOR:	Milk-White	TYPE:	Acrylic Polymer
FORM:	Liquid	SOLID CONTENT:	25%
SCENT:	Mild Solvent/Polymer	INITIAL GLOSS:	High
pH:	8.0 - 9.0	RECOAT DRYING TIME:	Minimum 30 Minutes
FLASH POINT:	None	COVERAGE:	2500 - 3000 sq. ft.
FOAM:	None	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	0.57
STORAGE (Unopened):	1 Year @ R.T.	REMOVABILITY:	Excellent
BIODEGRADABLE:	Yes	SCUFF RESISTANCE:	Very Good
WEIGHT/GAL:	8.5	DETERGENT RESISTANT: ..	Very Good
SHIPPING CLASS:	None	HIGH SPEED BURNISH:	Yes
PACKAGING:	1 Gal., 5 Gal.	DILUTION:	Use As Is

XL 25 Gloss Floor Finish

WITHOUT Intersept®
Antimicrobial Protection



Aspergillus Mold

WITH Intersept®
Antimicrobial Protection

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2012 XL North, Fall River, MA 02722 USA

Questions or Comments:
888-530-2259

www.xlnorth.com

Another Great
Product By



Rev. 082012a