

As true Matte floor finish, **XL Matte Floor Finish** provides extreme clarity without the gloss. Leveling is not an issue with XL Matte while providing a durable protection. Infused with Intersept® makes this a must for LVT and Lingleum projects.

## WHERE TO USE

**XL Matte Floor Finish** offers a variety of surface applications including Vinyl, Linoleum and other Resilient Floors.

## **DIRECTIONS**

Sweep the floor first using a dust mop or hard surface vacuum. Prior to application, floor should be completely stripped of old finish and thoroughly rinsed. The floor should be completely dry before applying first coat and all subsequent coats. Do not use an air mover or fan to dry finish. Apply in thin coats, evenly. On unsealed floors, apply 3-4 coats. On cleaned or scrubbed floors, apply as needed. For best results use a microfiber pad to apply the finish. Allow the finish to cure for 24 hours before placing any heavy furniture on the floor. Do not slide furniture on finished floor.

## INTERSEPT® ANTIMICROBIAL

Intersept® is an antimicrobial preservative that protects the cured floor finish against a broad spectrum of bacteria and fungi, including odor - and stain-causing microorganisms.

Intersept® is registered with the EPA and meets stringent certification standards set by the three most recognized testing protocols related to indoor environmental quality – the State of Washington Protocol, CRI Green Label and GSA Antimicrobial Certification. Yet, despite its proven ability as a microbial inhibiting preservative. **Intersept**® is low in toxicity and contains no arsenic, heavy metals, phenols or formaldehyde.

## **TECHNICAL SPECIFICATIONS**

COLOR:	. Milk-White
FORM:	. Liquid
SCENT:	. Mild Solvent/Polymer
pH:	. 8.0
FLASH POINT:	. None
FOAM:	. None
VISCOSITY:	. Water Thin
STORAGE (Unopened):	. 1 Year @ R.T.
BIODEGRADABLE:	. Yes
WEIGHT/GAL:	. 8
SHIPPING CLASS:	. None
PACKAGING:	. 4x1 Gal. Case, 5 Gal. Pail

TYPE:	Acrylic Polymer
INITIAL GLOSS:	N/A
RECOAT DRYING TIME:	Minimum 30 Minutes
COVERAGE:	2500 - 3000 sq. ft.
LEVELING:	Excellent
SLIP COEFFICIENT:	0.57
REMOVABILITY:	Excellent
SCUFF RESISTANCE:	Very Good
DETERGENT RESISTANT:	Very Good
HIGH SPEED BURNISH:	Yes
DILUTION:	Use As Is

FOR COMMERCIAL AND INDUSTRIAL USE ONLY

©2012 XL North, Fall River, MA 02722 USA

**XL Matte Floor Finish** 

WITHOUT Intersept® **Antimicrobial Protection** 

WITH Intersept®

Antimicrobial Protection