

# Single Channel Audio Cable

Complete line of Audio cables to fit every application imaginable

Part Number	Description	No. of Conductors	Conductor Gauge & Stranding	Shield Type & % Coverage	Overall Diameter (inches)	Nominal Cap. <sup>1</sup> (pf/ft.)	Nominal Cap. <sup>2</sup> (pf/ft.)	Jacket Thickness (inches)	Insulation Thickness (inches)	Weight per 100 ft. (lbs.)
WSNPVC	Whirlwind Exclusive Accusonic+1: Heavy duty, flexible single conductor cable with polyethylene insulation and black PVC jacket.	1	20, 42x36	T.C. Braid 78%	0.237	N/A	35	0.043	0.04	3.2
W9394	Belden 9394: Small diameter single conductor cable with rubber insulation and black neoprene jacket.	1	20, 27x34	T.C. Serve 95%	0.19	N/A	55	0.035	0.03	2.6
WMKPVC	Whirlwind Exclusive Accusonic+2: Heavy duty, flexible two conductor cable with polyethylene insulation and black PVC jacket.	2	22 26x36	B.C. Braid 78% .	0.245	19	35	0.045	0.018	3.2
W8412	Belden 8412: Two conductor cable with rubber insulation and black EPDM jacket.	2	20, 26x34	T.C. Braid 85%	0.262	30	55	0.041	0.019	4.5
W8413	Belden 8413: Small diameter two conductor cable with EPDM insulation and black IPDM jacket.	2	24, 45x40	T.C. Braid 56%	0.199	30	55	0.017	0.016	2.5
W8451	Belden 8451: Two conductor hookup wire with polypropylene insulation and gray or black PVC jacket.	2	22, 7x30	Beldfoil 100%	0.135	34	67	0.02	0.008	1.7

# Single Channel Audio Cable

W1266A	Belden 1266A Polypropylene insulation for jacket, 9 colors. 2 conductor hookup.	2	22, 7x30	Foil 100%	0.145	30	54	0.02	0.01	1.57
W1266A	Belden 1266A Polypropylene insulation for jacket, 9 colors. 2 conductor hookup.	2	22, 7x30	Foil 100%	0.145	30	54	0.02	0.01	1.57