Positive engagement, without excess wear



Data Sheet





Progress Capture, used

during lifting

For lowering

ISIC Solutions in Metal

The HaulerBiner Rescue is a compact kit, which can be worn on the harness and used for Pick-off Rescue in work at height and rope access rescues. The HaulerBiner can also be used to easily adjust the orientation of a stretcher and can be used for shorthaul tensioning.

The HaulerBiner device has a theoretical mechanical advantage of either 6:1 or 7:1, depending on the orientation the device is used in.

The pulley wheels are mounted in the body of the Karabiner, keeping them clear of the anti-tangle mesh outer, preventing it from jamming the wheels). Due to the in-Karabiner wheel mounting, the HaulerBiner kit is very compact when fully contracted, giving maximum haul height.

Height of Lift (HOL) [A]	Maximum 1m (43 ^{1/2} ") (Other HOL lengths available)
Length (fully contracted) [B]	32cm (12")
Mechanical Advantage	6:1 or 7:1
Weight (packed in pouch)	575g (1.2lb)
Rated Load	140kg (308lb)
Rope Size	6mm (1/4″)
Body Material	Aluminium (Anodised)
Gate Type	Supersafe (Triple-lock)
MBS	16kN (3596lbf)
Standards	Meets EN12278, EN567, EN362, EN1496

climb. work. rescue