

SIGHT MARK[®]



SPECIFICATIONS

Reticle type	2 MOA Dot
Reticle color	Red
Illuminated reticle	yes
Brightness settings	off, NV1, NV2, 3-10
Magnification	1x
Window dimension	28mm
Window material	glass
Eye relief	unlimited
Elevation adjustment MOA	120
Windage adjustment MOA	120
MOA adjustment (one click)	1/2
Finish/color	Matte black
Body material	Aluminum 6061 / rubber
Maximum recoil	500
IP Rating (waterproof)	IP67- submergible to 1m
Shockproof	yes
Fog proof	yes
Lens coatings	AR red
Mount type	weaver/picatinny
Battery type	AA
Battery life	670 -2,000,000 / 50,000 setting 6
Battery voltage	1.5V
Operating temp (°F)	-22 to 122
Length	4.4 / 113.5 (in/mm)
Width	2.9 / 75.1 (in/mm)
Height	2.6 / 65.3 (in/mm)
Weight	12.3oz

Wolverine FSR Reflex Sight

FEATURES

- ✦ Powered by a single AA battery
- ✦ Very low power consumption
- ✦ Digital switch brightness controls
- ✦ Scratch resistant, anti-reflective lens coating
- ✦ 28mm objective lens for quicker acquisition
- ✦ Protected adjustment caps
- ✦ Rubber armored, single piece 6061-T6 aluminum housing
- ✦ Adjustable mount height
- ✦ IP67 waterproof rating - submergible to 1m/3ft
- ✦ Fogproof, nitrogen purged
- ✦ Night vision compatible
- ✦ Unlimited eye relief
- ✦ Shockproof design
- ✦ Wide range of operating temperature, -22 to 122 F

INCLUDED

- ✦ Rubber lens
- ✦ Picatinny mount
- ✦ Riser for absolute cowitness

Designed for quick-target acquisition in short-range engagements, the Wolverine FSR delivers unlimited eye relief on an AR platform. Compact and light, yet exceptionally durable with a battery life for advanced then comparable models, this red dot sight is built for a lifetime of use.