

Unitech's HT680 is a compact and aggressive rugged mobile computer ideally suited for manufacturing, retail, logistics and transportation. Designed for the toughest work environments, the HT680 gives you the reliability and flexibility needed to increase productivity and efficiency in all of your data collection applications.

Durable Design

The HT680 is built to last, protecting your investment and minimizing downtime. Compact and rugged, the HT680 is IP54 rated, safeguarding it from moisture and dust. The HT680 can withstand multiple 6-foot drops to concrete and features gold plated non-rusting connector pins.

Maximum Productivity

The HT680 weighs less than a pound, has a 12-hour battery life and is ergonomically designed for one-handed operation making it perfect for scan-intensive applications such as warehousing. Its 22-key backlit keypad makes data entry simple.

Mobile and Versatile

The HT680 is available with a 1D laser or 2D imager smart scanner. Configuration and integration of the HT680 is fast and easy with its Microsoft Windows CE 5.0 Professional Plus operating system and Marvell PXA270 520MHz CPU. The HT680 is equipped with Bluetooth 2.0 and EDGE-GPRS connectivity as well as CCX4 WLAN roaming capability, making it perfect for mobile applications.

Main Features

- Microsoft Windows CE 5.0 Professional Plus
- Marvell PXA270 520MHz CPU
- Integrated 1D laser / 2D imager (optional) scan engine
- 30 degree scanning tilt
- EDGE-GPRS*, 802.11 b/g and Bluetooth 2.0 connectivity (WWAN models are a custom configuration)
- Mini SD and SDHC memory card
- Gold plated non-rusting connector pins
- IP54 rated
- 1.8-meter / 6-foot drop threshold



unitech

HT680 **Specifications**

Operation System

CPU	520MHz Marvell PXA270
Memory	SDRAM:128MB
	Flash ROM:512MB
OS	Microsoft Windows CE 5.0 Professional

Display

2.7" QVGA, Color Transflective TFT, with touch screen & backlight

Keypad

22 Keys, including 4-direction, function, and numeric keys.

Indicator

LEDs, Vibrator

Symbologies

1D laser (optional)

UPC-A/E, EAN-8/13, Codabar, Code 39, Code 39 full ASCI, Code 93, Code 32, Interleaved & Std. 2 of 5, EAN 128, Code 11, Delta, MSI/Plessey,Code 128, Toshiba.

2D imager (optional)

1D codes

Australian Post, British Post, Canadian Post, Codabar, Code 11, Code 128 Code 39, Code 93, EAN13, EAN8, IATA 2 of 5, ITF, ISBT, Japanese Post, Kix code(nl), Matrix 2 of 5, MSI, PLanet Code, Postnet, RSS expended, RSS Limited, RSS14, UPC A, UPC E, UPC E1

2D codes

Aztec, Codablock F, Code 49, Datamatrix, EAN-UCC, Composite, Maxicode, Micro PDF417, PDF417, QR Code, Tcif Linked C39..More

Communication

USB USB 1.1 Host & Client IEEE 802.11b/g , CCX4 Compliant WLAN PAN Bluetooth 2.0 Class 2 *WWAN eGPRS Ouad-Band GSM 850/900/1800/1900 MHz EDGE (e-GPRS) Multislot Class 10 GPRS Multislot Class 12 GSM Release 99 *WWAN models are a custom configuration





Los Angeles http://www.ute.com e-mail: inquiry@ute.com Houston, Mexico http://latin.unitech-adc.com e-mail: info@latin.ute.com

Unitech Asia Pacific & Middle East Taipei

http://www.unitech-utp.com.tw e-mail: aidcsales@tw.ute.com

Unitech Japan Tokyo

http://www.unitech-japan.co.jp e-mail: sales@unitech-japan.co.jp

Audio Speaker

Expansion Slot

Mini SD Power Source

Main Battery Backup Battery

Enclosure

Weight Dimension

Environmental

Operating temperature Storage temperature Relative Humidity Drop test to Concrete Environmental Sealing

Software

Microsoft Visual Studio 2005 Unitech HT680 SDK Oracle Database Lite

Accessories

USB communication and charging cable AC adaptor (with regional power cord) *4000mAh battery and battery door *Single slot desktop USB cradle *Please check with Unitech regional office for availability

Regulatory Approvals

CE, FCC, BSMI, VCCI, CCC, RoHS compliance

Unitech Europe Tilburg / Netherlands http://www.unitech-europe.com e-mail: sales@unitech-europe.com

Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen http://www.ute.com.cn http://www.ute.cn unitech@cn.ute.com Taipei http://adc-utt.unitech.com.tw barcode@tw.ute.com

Head Office

Taipei http://www.unitech-adc.com e-mail: marketing@tw.ute.com

Specifications subject to change without notice. Copyright 2009 Unitech Electronics Co., Ltd. All rights reserved. Unitech is a registered trademark of Unitech Electronics Co., Ltd. All product and company names are trademarks, service marks, or registered trademarks of their respective owners

14º F to 122º F -4º F to 140º F 5% ~ 95% (non-condensing)

6.69" H x 2.1" W x 1.18" D

Mono speaker, 90db@ 4-inch distance

8.14 Watt-Hour 3.7V@2200 mAh 16.28 Watt- Hour 3.7V @4.400mAh

Backup capability over 72 hrs

Supports SDHC

11.2 ounces

6-foot IP54

