



# MS250

## Reliable scanning you can trust

Delivering reliable and superior data capture, MS250 contact to middle range CCD scanner offers excellent performance for increasing productivity even when the barcodes are damaged or poorly printed. This cost-effective and reliable handheld scanner provides the optimum combination of performance which makes it an ideal scanning tool for a wide range of market applications, such as point-of-sale, document processing, personal data identification and inventory control.

### Easy to operate, User friendly design

MS250 is so easy to operate, just plug-and-play and connecting it to your computer with USB cable. There is no need to do any additional installation or training and it's all set and ready to work. Moreover, featuring slim size to ensure users comfort, it is also built in extra loud beeper (90dBa) that confirms positive decode feedback in noisy environments.

### Aggressive Scanning Capabilities

With powerful data capture performance to boost the scan speed up to 200 scans per second, MS250 handheld scanner supports reading depth from contact to 90mm and reading width to 80mm, which helps users to streamline workflow and increase efficiency. In addition to be equipped with advanced scanning technology, MS250 enhances the maximum compatibility by reading major 1D barcode types including GS1 dataBar symbology, as well as damaged or poorly printed bar codes.

### Cost-effective and Reliable

Designed to work in retail market, built in large trigger which allow user to use it easily, MS250 contact to middle range CCD scanner provides a cost-effective option and is reliable to be used everyday. Furthermore, it offers multiple interface options: Keyboard wedge, USB, RS232 and USB emulation com port driver. With versatile capabilities, MS250 is truly an affordable barcode scanner with high value.

### Features

- Aggressive scan rate: up to 200 scans/sec
- Lightweight and ergonomic design
- Available to read most 1D barcode types including GS1 dataBar symbology
- Multi-interface Communication : USB, K/W, RS232 and USB emulation com port driver
- Support minimum resolution 3mil/0.076mm
- Dual color for choice (dark blue and beige)



### Optical & Performance

|                                   |   |
|-----------------------------------|---|
| Receiving Device                  | Linear CCD Sensor   |
| Light Source                      | Visible Red light 635nm LED   |
| Max. Resolution                   | 3mil (0.076mm) @ PCS90%   |
| Scan Rate                         | 200 scans/ second $\pm 10\%$  |
| Printing Contrast Scale           | 45%   |
| Sensor                            | Linear Imager   |
| Ambient Light                     | 20,000 Lux Max  |
| Scan Angle                        | *Test Conditions : Code 39, 10mil/0.25mm, PCS 90%                       |
|                                   | Forward & Backward $\pm 10^{\circ} \sim 30^{\circ}$ ( $\pm 5^{\circ}$ ) |
|                                   | Left & Right $\pm 60^{\circ}$ ( $\pm 5^{\circ}$ )                       |
| Width of Field                    | 80mm  |
| Reading Distance<br>(DOF PCS=90%) | Up to 90mm @ 20mil, PCS90%, Code39                                      |

### Electrical

|                     |  |
|---------------------|--|
| Operation Voltage   | 5VDC   |
| Current Consumption | Operation mode:<120mA;<br>Standby mode:<20mA |

### Mechanical

|                   |                         |
|-------------------|-------------------------|
| Housing Material  | ABS                     |
| Switch life       | 1 million times         |
| Scanner Dimension | 163.3mm x 79mm x 62.5mm |
| Scanner Weight    | 83g                     |

### Environmental

|                       |   |
|-----------------------|---|
| ESD Protection        | Functional after 8K Contact and 12K Air |
| Operating Temperature | 0°C to 50 °C (32 °F to 122 °F)          |
| Storage Temperature   | -20 °C to 70 °C (-4 °F to 158 °F)       |
| Relative Humidity     | 20% to 95% (Non-condensing)             |
| Mechanical Shock      | 1.5m onto concrete (scanner only)       |

### Communication

USB, RS232, Keyboard Wedge, USB emulation COM port

### Functionality

|                      |  |
|----------------------|--|
| Symbologies          | UPC-A/UPC-E, EAN-8/EAN-13, Industrial 2 of 5, Codabar, Matrix 2 of 5, Code 11, Code 93, Code 32, Code 128, Full ASCII Code 39, Interleaved 2 of 5, China Postal Code, MSI Plessey Code, EAN/UCC 128, Telepen Code, IATA Code, GS1 Databar. |
| Operation Mode       | Trigger Mode, Flash Mode   |
| Data Formatting      | Prefix, Suffix, Code ID  |
| Configuration Method | Configuration barcodes   |

### Regulation Approvals

CE, FCC, BSMI, VCCI



#### Unitech America

Los Angeles, Houston  
<http://us.ute.com> e-mail: [info@us.ute.com](mailto:info@us.ute.com)  
<http://can.ute.com> info@can.ute.com  
 Mexico  
<http://latin.ute.com> e-mail: [info@latin.ute.com](mailto:info@latin.ute.com)

#### Unitech Asia Pacific & Middle East

Taipei  
<http://apac.ute.com> info@apac.ute.com / info@india.ute.com  
<http://mideast.ute.com> info@mideast.ute.com

#### Unitech Japan

Tokyo  
<http://jp.ute.com> e-mail: [info@jp.ute.com](mailto:info@jp.ute.com)

#### Unitech Europe

Tilburg / Netherlands  
<http://eu.ute.com> e-mail: [info@eu.ute.com](mailto:info@eu.ute.com)

#### Unitech Greater China

Beijing, Shanghai, Guang Zhou, Xiamen  
<http://cn.ute.com> info@cn.ute.com  
 Taipei <http://tw.ute.com> info@tw.ute.com

#### Headquarters

Taipei, Taiwan  
<http://www.ute.com> e-mail: [info@hq.ute.com](mailto:info@hq.ute.com)