

Compact Intelligent MagStripe Swipe Reader

Full Functionality & Compact Size

The MiniMag Intelligent Reader delivers exceptional performance in brilliantly designed housing. It can read up to three tracks of magnetic stripe card data regardless of swiping direction or speed which increases usability. MiniMag's compact footprint is ideal for POS, security, loyalty and other applications where space is limited.

Easy to Use & Install

The uniquely designed flat surface allows for mounting in different orientations using threaded inserts or Velcro[®]. The cable can exit through the side or bottom which provides flexibility in mounting options.

Multiple Interfaces to Meet Your Needs

MiniMag is an intelligent swipe reader with six communication interfaces: keyboard (PS/2) wedge, USB keyboard, USB HID, RS-232, RS-232 Port Powered, and USB CDC serial interfaces. JPOS and OPOS drivers are also available.

Many Programmable Features

The MiniMag is a fully programmable reader. Reader output format can be customized with user-friendly, Windows-based MagSwipe Configuration Utility. For example, after reading and validating card data, the unit can be programmed to parse the data, insert control characters, and add prefix/suffix characters while maintaining data integrity through vertical and longitudinal error checking. The reader also includes language options to ensure that the correct data is sent to the terminal.

Features and Benefits

- Interfaces: Keyboard, RS-232, RS-232 Port Powered, USB keyboard, USB CDC, or USB HID
- User-friendly configuration software, simplified data editing and configuration
- Discriminates card data formats between AAMVA and CA DMV
- · Reads up to three tracks of information
- Reliable MagStripe reader for a minimum of one million card swipes
- Clear identification of successful card reads with a beeper and LED indicators
- Can be used free-standing or mounted to work with a variety of applications
- Threaded inserts for easy and flexible mounting



alue through Innov

MiniMag[™]Specifications IDMB-33XXXX

Electrical

Power Requirements:

Interfaces.

+5 VDC +/-10%, 50mV ripple Max. Keyboard (PS/2), 40mA Max. RS-232, 70mA Max. USB-HID, USB-CDC, and USB-KB, 70mA Max Keyboard (PS/2), RS-232, RS-232 Port Powered, USB-KB, USB-HID, USB-CDC

Environmental

Operating Temperature: Storage Temperature: Humidity:

Reliability

Operating Life: Warranty:

Mechanical

Media Thickness: Media Formats: Slot Width: Swipe Speed: Dimensions(L)x(W)x(H): Weiaht: Indicators: Cable Length: Cable Connector:

Footprint:

0°C to 55°C (32°F to 131°F) -30°C to 65°C (-22°F to 149°F) Maximum 95% non-condensing, dry storage

1,000,000 cycles minimum Two years, parts and labor

0.015 inches (0.381mm)to 0.038 inches (1.14mm) ISO 7811, AAMVA, and other F2F formats 0.040 inches (1.37mm) 3 to 60 inches per second, bi-directional 3.54 inches (90mm) x 1.34 inches (34mm) x 1.10 inches (28mm) 4.6 oz. Tri-colored LED, beeper (excluding on port-powered model) 6-foot side exit cable (Bottom exit is an option) Keyboard - 6 pin mini-DIN, RS-232 DB9F



Value through Innovatior

Corporate Headquarters: 10721 Walker Street, Cypress, California 90630 www.idtechproducts.com (714) 761-6368 sales@idtechproducts.com

International Sales Office for Canada & South America: +450 465 5261 (Canada) robertop@idtechproducts.com

> **European Sales Offices:** +49(0) 8851 6159900 (Germany) emea@idtechproducts.com

> > **ISO 9001 Certified**

USB

FC

©2012 International Technologies & Systems Corporation. ID TECH is a registered trademark of International Technologies & Systems Corporation. MiniMag and Value through Innovation are trademarks of International Technologies & Systems Corporation. All specifications subject to change without notice.

80066504-001 R09/12