**P210** 

## P200 SERIES CARD PRINTERS



### . . . . . . . .

Color and Monochrome printing	
Print speed:	Under 30 sec per card (YMCKO) 4 sec per card (K)
Resolution:	300 dpi (12 dots.mm)
Print method:	Dye sublimation Thermal Transfer



# Full Color Plastic Card Printing Is Easier And More Economical Than Ever Before.

The P210 can be used to add personalization to preprinted cards, or to print on blank plastic cards in full color or monochrome black. Designed for single-sided edge-to-edge color printing, the P210 produces rich, vibrant color, with 300 dpi resolution for precise readable bar codes, photos, graphics, and text.

Use the P210 for:

- Adding text, bar codes or other personalization to preprinted plastic cards
- Printing plastic gift cards and membership cards
- Issuing photo ID badges

The Eltron P210 is ideal for printing personalized plastic cards in on-demand applications. Its ultra-quiet operation and small footprint makes the P210 well suited for countertop applications where work space is at a premium. Operator friendly features include front card loading and output, a quick-load ribbon cartridge for fast ribbon replacement, and an easy-to-change cleaning cartridge that thoroughly remove dust before cards are printed.

Options include a magnetic stripe encoder for card applications that require encoded information. The P210 comes with two dual interfaces; USB and Parallel, or USB and Serial, for easy integration into any system.

Eltron Plastic Card Printers are designed and manufactured to exacting ISO 9001:2000 standards for the utmost in quality and dependability, and sold through a worldwide network of over 100 authorized resellers.

# P210 Specifications

## **General Specifications**

- Under 30 sec per card, full color single sided printing (YMCKO) .
- Card feeder capacity: 50 cards (30 mil) •
- Card Output Hopper capacity: 20 cards (30 mil) .
- 2MB of Standard Memory, 1 MB Flash .
- Small footprint •
- OpenACCESS<sup>™</sup> clamshell design (Patent Pending) .
- Convenient front card loading and output •
- One 3-state LED and incorporated Multi-Function Button
- Windows Drivers for 95/98, 2000 and NT 4.0
- Bi-directional driver communication •
- Powerful EPCL (Eltron Printer Command Language)

## **Color Printing**

- Color dye sublimation or monochrome thermal transfer printing
- Under 30 seconds per card (YMCKO)
- 300 dpi (11.8 dots/mm) print resolution

## **Bar Codes**

- Code 39 •
- Code 128 B & C with & without check digit
- 2 of 5 & 2 of 5 Interleave •
- UPC-A .
- EAN 8 & EAN 13 .
- PDF-417 2D bar code

## Fonts

- Resident: Arial Bold 100
- TrueType fonts available via Windows driver

## **Card Specifications**<sup>1</sup>

- Types: PVC & Composite PVC .
- Card width/length: ISO CR-80 ISO 7810, 2.125" (54mm) X 3.385" (86mm)
- Option: Magnetic Stripe ISO 7811 .
- Card thickness: 30 mil





ISO 9001

© 2002 7IH Corn

All Rights Reserved. Specifications subject to change without notice. All Copyrights,OpenACCESS™, Eltron and TrueColours are trademarks of Zebra Technologies Corporation. Arial is a registered trademark of The Monotype Corporation. Microsoft and Windows are registered trademarks of Microsoft Corporation.



#### Headquarters

Zebra Technologies Corporation 1001 Flynn Road Camarillo, CA 93012-8706 U. S. A. Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@eltron.com

## **Ribbon Specifications**<sup>2</sup>

- **Ribbon Cartridge required**
- Black Monochrome: 500 cards/cartridge
- YMCKO: 100 cards/cartridge
- Auto ribbon detection system



## **Bi-directional Communication Interface**

- Centronics Parallel and USB
- RS232 Serial and USB



### Mechanical

## Without Card Feeder

- Width: 7.16" (182mm)
- Depth: 9.44" (240mm) •
- Height: 7.1" (180mm) •
- Weight: 6.4 lbs (2.9kg) •

## Electrical

- 110 230 Volts AC, 50/60 Hz
- FCC Class A, CE, UL and CUL approved

## Environmental

- Operating Temperature: 60°F to 86°F (15°C to 30°C) •
- Operating humidity: 20% to 65% non condensing
- Storage temperature: -23°F to 158°F (-5°C to 70°C)
- Storage Humidity: 20% to 70% non-condensing
- Ventilation: Free air

## Options

Magnetic stripe encoder


Note 1: Recommended types of cards.

Note 2: For optimum performance always use Eltron TrueColours Certified Media.



Europe

Zebra Technologies Corporation Zebra House The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 (0) 870 241 1527 Fax: +44 (0) 870 241 0765 e-mail: eurosales@eltron.com



Asia Pacific

Zebra Technologies Corporation 1 Sims Lane #06-11 387355 Singapore Telephone: +65 6842 0322 Fax: +65 6842 0514 e-mail: asiasales@eltron.com

## www.eltroncards.com





- Width: 7.16" (182mm)
- Weight: 6.4 lbs (2.9kg)
- Depth: 11.9" (303mm) Height: 7.1" (180mm)