

P520



P SERIES CARD PRINTERS



Dual-Sided Color Card Printer with Built-in Laminator Provides Fast, Easy Production of Long-life Plastic Cards

The P520 is a robust, high-speed card printer designed to quickly produce ISO flat cards for high durability and secure applications. The P520 features an all metal enclosure that houses a fast, field-proven print engine, and heavy-duty fourth generation Lx4 card laminator performance tuned for the P520 print engine. The P520 is ideal for producing:

- Secure Facility Access Control and Auto-ID cards
- Law Enforcement & Correction Facility ID cards
- Driver's Licenses and Government ID cards
- Student Identification and Time & Attendance cards

Laminating considerably increases card life and durability. Lamination can prolong card life by 2 to 5 additional years when compared to non-laminated cards under similar conditions.

The P520 printer/laminator is ultra-quiet and fast, printing and lamination up to 125 cards per hour. It is designed to print and laminate both sides of a card for dual-sided applications.

A user-friendly LCD display indicates unit status, settings and maintenance functions. Control buttons allow quick, easy access to menu options. The card feeder cover can be opened during operation to reload cards for continuous production.

Other advanced features include automatic ribbon and laminate synchronization, an in-line cleaning cartridge, optional magnetic encoding and/or Smart Card contact stations, a reject hopper for cards that fail encoding, and both Centronics and USB interfaces. Windows® drivers, compatible with Windows NT, 95/98, 2000, provide convenient plug and play operation.

Eltron Plastic Card Printers are designed and manufactured to exacting ISO 9001:2000 standards for the utmost in quality and dependability, and sold through a worldwide network of over 100 authorized resellers.

• • • • •
Dual-sided monochrome and full-color card printing and laminating

Print speeds: 125 cards/hour
(YMC with 1.mil lamination)

110 cards/hour
(YMCK with 1.mil lamination)

95 cards/hour
(YMCK/K with 1 mil lamination)

Resolution: 300 dpi (12 dots/mm)

Print method: Dye sublimation
Thermal transfer

P520 Specifications

General Specifications

- High speed printer with built-in laminator
 - YMC w/1.0 mil lamination 125 cards/hour
 - YMCK w/1.0 mil lamination 110 cards/hour
 - YMCK-K w/1.0 mil lamination 95 cards/hour
- Dual process system (while one card prints second card is laminated)
- Dual sided printing with flip over capability
- Dual sided lamination capability
- Card cooling system produces true ISO flatness of laminated cards
- Enclosed 100 (30mil) card capacity card feeder that can be opened during operation for continuous throughput
- Metal enclosure with transparent viewing window
- Two line 32 digit interactive menu driven control panel
- Encoded card reject hopper
- Windows drivers for 95/98, NT, and 2000
- Centronics parallel and USB interface (standard)
- One year printer warranty with Hot Swap
- One year (Unlimited passes) print head warranty¹
- Powerful EPCL (Eltron Printer Command Language)

Color Printing & Lamination

- Color dye sublimation or monochrome thermal transfer printing
- 300 dpi (12 dots/mm) print resolution
- Enhanced 4 fourth generation laminator with auto laminate synchronization

Bar Codes

- Code 39, Code 128 B & C with & without check digit
- 2 of 5 & Interleaved 2 of 5
- UPC-A
- EAN-8 & EAN-13
- PDF-417 2D bar code and other symbologies available via Windows™ driver

Fonts

- Resident: Arial Normal 22, Arial Bold 28
- True Type fonts available via Windows™ driver

Card Specifications²

- Types: PVC, Composite (use 30 mil Composite cards when laminating)
- Card width/length: ISO CR-80, 2.125" (54mm) X 3.385" (86mm)
- Card thickness: .76mm (30mil)
- Card feeder capacity: 100 cards (30mil)
- Card output hopper capacity: 100 cards (30mil)

Note 1: One year warranty applies to Floating Bracket System (FBS) printhead only.

Note 2: For optimum performance, use Zebra/Eltron approved media.

Ribbon Specifications²

- Monochrome: 1000 and 1500 cards/roll
- Monochrome colors: black, red, blue, green, silver, gold, white
- K Resin + O: 500 cards/roll
- K Dye + O: 500 cards/roll
- YMC: 300 cards/roll
- YMCK: 250 and 400 cards/roll
- YMCKO: 200 and 350 cards/roll
- YMCKK: 200 cards/roll
- YMCKOK: 170 cards/roll



Overlamine Specifications

- 0.6 to 1 mil Clear overlamine roll, 175 (0.6 mil) & 100 (1.0 mil) cards/roll
- 0.6 to 1 mil Clear overlamine for smart cards and magnetic stripe cards, 175 (0.6 mil) & 100 (1.0 mil) cards/roll
- 0.6 to 1 mil overlamine with hologram, 175 (0.6 mil) and 100 (1.0 mil) cards/roll
- 1.0 mil Clear overlamine alternating (full & mag stripe) 50 cards/roll

Communications Interface

- Centronics Parallel standard (parallel cable included)
- USB standard (USB cable-not included)



Mechanical

- Width: 32.75" (832mm)
- Depth: 9.25" (235mm)
- Height: 10.43" (265mm)
- Weight: 47 lbs (21.45kg)

Electrical

- 100-250V, 50/60Hz
- FCC Class A, CE, UL and CUL approved

Environmental

- Operating temperature: 60°F to 86°F (15°C to 30°C)
- Operating humidity: 20% to 65% non-condensing
- Storage temperature: -23°F to 158°F (-5°C to 70°C)
- Storage Humidity: 20% to 70% non-condensing
- Ventilation: Free air

Options


- Smart card contact station (30 mil cards only)
- Magnetic encoder (30 mil cards only)
- Extended warranty program
- On-Site warranty program and Depot warranty programs
- Cleaning supplies



Access Control



Driver's Licences



Security ID



Corporate Identity



Zebra Technologies International, LLC



©2002 ZIH Corp.
All Rights Reserved. Specifications subject to change without notice. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Headquarters

Zebra Technologies Corporation
1001 Flynn Road
Camarillo, CA 93012-8706
U. S. A.
Telephone: +1 805 579 1800
Fax: +1 805 579 1808
Toll free in US: 800 452 4056
e-mail: cards@eltron.com

Europe

Zebra Technologies Corporation
Zebra House
The Valley Centre, Gordon Road
High Wycombe
Buckinghamshire HP13 6EQ, UK
Telephone: +44 (0) 870 241 1527
Fax: +44 (0) 870 241 0765
e-mail: eurosales@eltron.com

Asia Pacific

Zebra Technologies Corporation
1 Sims Lane #06-11
387355 Singapore
Telephone: +65 6842 0322
Fax: +65 6842 0514
e-mail: asiasales@eltron.com

www.eltroncards.com