

## CRD3301

Cradle for OPR3301



### + Specifications

#### Communication

- RS232: 600 bps - 57.6 kbps
- Bluetooth: Ver. 1.2, output power class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption
- USB: Ver. 1.1, client, HID, USB-A connector

#### Power

- Voltage requirement: 6V  $\pm$  5%
- Battery charging time: Max. 5 hours with power supply, max. 10 hours with USB bus power

#### Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 25 - 85% (non-condensing)
- Humidity in storage: 20 - 90% (non-condensing)

#### Physical

- Dimensions (w x h x d): 100 x 78 x 185 mm / 3.94 x 3.07 x 7.28 in
- Weight body: Ca. 240 g / 8.5 oz
- Case: ABS, Black or White

#### Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS, EN300 328, EN301 489

#### Enclosed items

- USB cable
- RS232 cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Spain:** Valencia  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire  
- **U.S.A.:** Renton, WA  
- **Japan:** Warabi City

- **Taiwan:** Taipei  
- **P.R.China:** Shanghai  
- **Australia:** Kariang  
- **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com

# OPTICON

WWW.OPTICON.COM