

Magellan® 1400i

Omni-Directional Imaging Scanner



Features:

- Aggressive imaging performance and intuitive operation reduces checker training and speeds checkout for better customer service
- Autodiscriminates PDF and 1D bar codes
- New imaging technology eliminates moving parts associated with laser scanners for improved reliability
- Targeted scanning mode for PLU Lists
- Hands-free scanning for small, easily handled items, handheld scanning for bulkier items
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Small footprint and size allow for easy integration into point-of-sale
- Textured rubber grip area and small size allow hands of all sizes to comfortably hold the scanner when needed
- Checkpoint® Systems EAS compatible
- Tilting stand allows scan volume to be optimized for each user and has screw holes for fixed mounting
- Standard product is available in either Black or Light Grey. Other colors and custom logo options are available for a minimum quantity purchase. Please contact PSC or your PSC reseller for more information on this service.

Mechanical

Dimensions (Scanner with Stand):

Height: 71.3" / 181 cm
 Width: 3.23" / 8.2 cm
 Length: 3.82" / 9.7 cm

Weight: 15.7 oz / 345.4 g

Environmental

Temperature Rating

Operating: 32° to 104° F / 0° to 40° C
 Storage/Transport: -40° to 158° F / -40° to 70° C

Humidity: 5 to 95% NC (non-condensing)

Shock: Multiple 4' / 1.2 m drops

Water & Dust Resistance: IP52

Electrical

Operating Voltages

5.0V model ± 5%
 8.0 – 14.0V model

Operating Current (idle): < 350mA

Operating Current (label read): < 450mA

Communications

- RS-232
- OEM USB
- Wand Emulation
- USB
- Keyboard Wedge
- IBM 46xx / RS-485

Optical

Scan Pattern: 100 line

Scan Rate: 1,100 (digital scan lines/second)

Single Line Activation: via button

Scan Volume: 80 in³ / 1311 cm³

Minimum Resolution: 5 mil

Print Contrast: 25%

Roll: 0 – 360°

Pitch: ±65°

Yaw: ±75°

Ambient Light

Indoor: < 557 foot candles / 6,000 Lux

Outdoor: < 7,999 foot candles / 86,100 Lux

Depth of Field: Please refer to table below

DEPTH OF FIELD Range Comparisons	
LABEL DENSITY	RANGE
5 mil	0.75 to 2.0' / 19 to 50.8 cm
6.6 mil (PDF)	1.5 to 3.0' / 38 to 76 cm
7.5 mil	0.5 to 4.0' / 13 to 10.2 cm
10 mil	0 to 6.0' / 0 to 15.2 cm
10 mil (PDF)	1.25 to 7.0' / 31 to 17.7 cm
13 mil (UPC)	0 to 8.0' / 0 to 20.3 cm
15 mil (PDF)	1.0 to 8.0' / 2.5 to 20.3 cm
20 mil	0 to 9.0' / 0 to 22.9 cm

Minimum distance determined by symbol length and scan angle.
 Printing resolution, contrast, and ambient light dependent.

Data Sheet

Decoding Capability

The Magellan® 1400i omnidirectional imaging scanner autodiscriminates between the following supported symbologies:

Retail Codes:

- EAN 8 & 13 with full expansion 8 to 13
- EAN/JAN two label
- JAN 8 & 13 with full expansion 8 to 13
- UCC/EAN 128
- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- Dual Bar Codes for Japan (2 label read)
- Italian Pharmacode
- PDF-417/Micro-PDF
- Reduced Space Symbology (RSS): RSS-14, RSS expanded, RSS Stacked (omni-directional), RSS Composites and RSS Limited
- Supports GTIN

Industrial Codes:

- Code 39 (with full ASCII)
- Code 128 (Up to 80 characters, including Code 39 conversions)
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Codabar
- MSI/Plessey

Please contact your PSC representative for other available symbologies.

Safety and Regulatory

Electrical: Gost R; TÜV; UL; cUL; NOM

Emissions: Complies to FCC; EN 55022; AS/NZS CISPR 22; VCCI; CNS 13438; ICES-003

Restriction of Hazardous Substances: Complies to EU RoHS



Other

EAS Compatibility: Integrated EAS hardware works with Checkpoint® Systems.

PSC Inc.
 959 Terry Street
 Eugene OR 97402-9150 USA
 Tel: 800 695 5700 or 541 683 5700
 Fax: 541 345 7140
www.psc.com



Copyright © PSC Inc. 2006. All rights reserved. • Protected to the fullest extent under US, and international laws. Copying or altering of this document is prohibited without express written consent from PSC. • PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The PSC logo and Magellan are registered trademarks of PSC Inc. • All other brand and product names are trademarks of their respective owners. • Additional information concerning this product or other PSC products and services can be found at the PSC web site: www.psc.com. • Product specifications are subject to change without notice.

