VALUE



- » 30 Sec/Card Full-Color, Single-Sided **Print Speed**
- 100 Card-Capacity Feeder
- 16-digit LCD Display
- » USB Communication
- » CardSense™ Single Card-Feed (Optional)
- » 3 Track HiCo/LoCo Magnetic Encoder, available in Stripe Up or Stripe Down (Optional)



The Zebra P110i is a reliable, compact and easy to use card printer that delivers outstanding performance at a great price.

The P110i gives you versatility and cost effectiveness for a wide variety of applications:

- » Employee ID and Access cards
- » Student and Faculty ID's
- » Membership cards
- » Personalized Loyalty and Gift cards

Zebra P110: Advantages

Versatile: Print in full color or monochrome. Choose automatic multi-card feed or CardSense™ single card feed. Compact, sleek design lets you put the P110i just about anywhere.

Easy-to-Use: Intuitive design reduces training costs. Blue touch points indicate user touchable features. Translucent card cover allows you to see when card supply is running low. No-tools-necessary printhead replacement.

Innovative Patent-Pending Technology: P110i uses high strength plastics and advanced electronics for reduced size and weight and outstanding performance. Easy to replace Load-N-Go™ ribbon cartridge with integrated card cleaning roller features automatic set-up and low ribbon warning indicator.

The Zebra P110i. Small printer, big statement.

Useries





P110i

Card Printer Product Specifications

COLOURS

General Specifications

- » Integrated card feeder
- » Load-N-Go™ drop-in ribbon cartridge
- » 16-digit LCD display
- » Zebra printer drivers for Windows® 2000 and Windows® XP
- » One year printer warranty
- » One year (unlimited passes) printhead warranty

Printing

- » Color dye sublimation or monochrome thermal transfer printing
- » 30 seconds per card full-color single-sided (YMCKO)
- » 300 dpi (11.8 dots/mm) print resolution

Bar Codes

- » Code 39, Code 128 B & C with & without check digit
- » 2 of 5 & 2 of 5 Interleaved
- » UPC-A, EAN 8 & EAN 13
- » PDF-417 2D bar code and other symbologies can be printed via Windows drivers

Card Specifications

- » Types: PVC, PVC Composite
- » Card width/length: ISO CR-80-ISO 7810, 2.12" (54mm) x 3.38" (86mm)
- » Magnetic Stripe-ISO 7811
- » Smart Card-ISO 7816
- » Card thickness: 30 mil (.76mm)
- » Card feeder capacity: 100 cards (30 mil)
- » Card output hopper capacity: 45 cards (30 mil)

Communications Interface

» USB 1.1 (cable included)

Ribbon Specifications*

- » Load-N-Go™ ribbon cartridge with integrated cardcleaning roller
- » ¿ Series ribbon information technology
- » YMCKO: 200 cards/cartridge
- » Monochrome: 1000 cards/cartridge in black, blue, or white

*for optimum printer performance use Genuine Zebra Supplies

Mechanical

- » Width: 7.9 in (201mm)
- » Depth: 12.9 in (328mm)
- » Height: 8.5 in (216mm)
- » Weight: 9.5 lbs (4.3kg)

Electrical

- » 110 ~ 240 Volts AC, 50 ~ 60 Hz (auto switching)
- » 16MB image memory standard
- » FCC Class B. CE. UL and CUL approved

Environmental

- » Operating Temperature: 60°F to 86°F (15°C to 30°C)
- » Operating Humidity: 20% to 65% non-condensing
- » Storage Temperature: 23°F to 158°F (-5°C to 70°C)
- » Storage Humidity: 20% to 70% non-condensing
- » Ventilation: Free air

Options

- » Magnetic encoder (30 mil cards only), 3 track Stripe Up or Down HiCo/LoCo (factory-installed)
- » CardSense™ single card-feed mode
- » Starter Kit (200 30 mil PVC cards and 1YMCKO ribbon)
- » Cleaning Kit (4 print engine and 4 feeder cleaning cards)

Genuine Zebra Supplies

» Your choice of card printer supplies is critical. It is a primary factor affecting the reliability and consistency of printing. Genuine Zebra Supplies meet stringent quality standards and are tested for optimum performance with Zebra card printers.

www.zebracard.com



An ISO 9001 registered company ©2005 ZIH Corp. Specifications listed are for base model printers with standard features only unless otherwise notes. Specifications subject to change without notice. All product and brand names are trademarks of their respective companies. All rights reserved. All Copyrights, Trade and Service Marks shown or depicted herein are registered by their owners. No infringement is made for or implied by the use thereof.

Part No. P1101-10/05

North America

Zebra Technologies Corporation Card Printer Solutions

1001 Flynn Road Camarillo, CA 93012-8706 USA

Telephone: +1 805 579 1800 Fax: +1 805 579 1808 Toll free in US: 800 452 4056 e-mail: cards@zebra.com

Europe, Middle East, Africa

Zebra Technologies Corporation

Card Printer Solutions

The Valley Centre, Gordon Road High Wycombe Buckinghamshire HP13 6EQ, UK Telephone: +44 870 241 1527 Fax: +44 870 241 0765

e-mail: eurosales@zebra.com

Asia Pacific

Zebra Technologies Corporation Card Printer Solutions

16 New Industrial Road #05-03 Hudson TechnoCentre Singapore 536204 Telephone: +65 6858 0722 Fax: +65 6885 0836 e-mail: asiasales@zebra.com

Latin America

Zebra Technologies Corporation Card Printer Solutions

9800 NW 41st Street, Suite 220 Doral, FL 33178 USA

Telephone: +1 305 558 3100 Fax: +1 305 558 8485 e-mail: latinsales@zebra.com