



SEE MORE. DO MORE.

# Specification Sheet

## Z-Select 4000D 7.5 mil Tag

### Features:

- Direct thermal, premium, topcoated, ultra smooth, 7.5 mil paper tag
- Excellent print quality
- Topcoating is suitable for fanfolding
- Available in white (05847RM)

### Suggested Applications:

- General purpose ticketing
- Shop floor tracking tickets
- Retail hang tags
- Parking garage tickets
- Work in process ticketing

### Material Construction:

Description		Caliper
Facestock	White smooth topcoated direct thermal paper	7.5 mil
		<b>Total</b> 7.5 mil +/- 10%

### Temperature Performance:

- Minimum Application Temperature: NA
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use

**Chemical Resistance**

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT			X	X	X												

NOTE: For guidance only, not to be used for setting specifications

**Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.