



🔍 click to enlarge image



Standard 2 NPT Inlet Cast Iron Gate Valves

Item Number# **8700E20**

[Write a Review](#)

\$59.95

~~\$67.95~~

(You Save 12%)

- [Description](#)
- [Specs](#)
- [You May Also Need](#)
- [Q&As](#)
- [Reviews](#)

Description

Standard 2 NPT Inlet Cast Iron Gate Valves For A Drums and Barrels with 2" Bung Hole

Features:

- Description: Standard
- Weight: 4 lbs.
- Description: 2" Aluminum gate valve
- NPT Inlet Size: 2 inch
- Fast flow control without splashing
- Padlockable handle
- Manual and self-closing models
- Ideal for applications requiring aluminum alloys
- Provides improved corrosion resistance for certain fluids

Fast flow control without splashing Padlockable handles Manual and self-closing models Excellent for dispensing non-flammable viscous liquids. Super rugged cast iron gate valves have a large, nearly straight bore with an oval discharge opening angled at 45-60 for fast flow of thick liquids without splashing.

The machined and lapped brass faceplate provides smooth operation and a perfect seal. Glossy black lacquer finish. Standard Gate Valve has short formed-steel handle.



NOTE: These gate valves are designed for liquids that have a minimum viscosity of 2,000 cPs.

Features: Description: Standard NPT Inlet Size: 2 in. Weight: 4 lbs.

Fast flow control without splashing Padlockable handle Manual and self-closing models Excellent for dispensing non-flammable viscous liquids. Super rugged cast iron gate valves have a large, nearly straight bore with an oval discharge opening angled at 45-60° for fast flow of thick liquids without splashing. The machined and lapped brass faceplate provides smooth operation and a perfect seal. Glossy black lacquer finish.

Standard Gate Valve has short formed-steel handle.

These cast aluminum gate valves are lighter and easier to use than cast iron gate valves. They have a large, nearly straight bore with an oval discharge opening angled at 45°- 60° for fast flow of thick liquids without splashing. The machined and lapped brass faceplate provides smooth operation and a perfect seal. Short, sturdy 2-inch black enamel finish metal stamped handle.

Note: These faucets are intended for use with non-flammable viscous liquids stored in or dispensed from non-pressurized containers at ambient room temperature.

NOTE: These gate valves are designed for liquids that have a minimum viscosity of 2,000 cPs.

BayTec Containers Item Number 8NS67

Specifications

- **DESCRIPTION:**Standard
- **WEIGHT:** 4 lbs.
- **DESCRIPTION:**2" Aluminum gate valve
- **NPT INLET SIZE:**2 inch
- **FAST FLOW CONTROL**without splashing
- **PADLOCKABLE** handle
- **MANUAL**closing models