

SLCBL Connection / Termination Kits

For use in ordinary locations with SLCBL cable only (UL approved).

For use in roof & gutter snow melting & de-icing applications with SLCBL cable only (UL approved).



Ordinary Locations

Approvals valid only when used with appropriate heating cable and installation accessories, and installed in accordance with all applicable instructions, codes, and regulations.

SLCBLUC: SLCBL Power Connection Kit



Kit Contents:

- | | |
|---|---|
| 2 Heat-trace warning labels | 1 Black heat-shrink tube
1/2" x 1" (13mm x 25mm) |
| 2 De-icing snow melt caution labels | 1 Green/Yellow heat-shrink tube
1/4" x 6" (6mm x 15cm) |
| 1 Standoff pipe mounting bracket | 2 Black heat-shrink tubes
1/8" x 5-1/2" (3mm x 14cm) |
| 1 Lock nut | 1 Sealing gasket |
| 1 1/2"NPT Seal fitting with strain relief and grommet | 1 End seal |
| 3 Wire nuts | |

Enough to complete:

One input power connection and one end seal termination.

NOTE: Junction box and pipe strap sold separately. Requires UL Listed junction box suitable for the location with a clearance hole for 1/2" conduit or 1/2" NPT thread hub. For heating cable with no outer-jacket (Type -B only), a metallic junction box must be used to ensure proper grounding.

SLCBLUC-GF: Ground Fault Power Connection Kit




Kit Contents:

- | | |
|---|---|
| 2 Heat-trace warning labels | 1 Heat-shrink tube
3/4" x 5" (19mm x 13cm) |
| 2 De-icing snow melt caution labels | 2 Heat-shrink tubes
1/8" x 1" (3mm x 25mm) |
| 1 Cloth tape | 1 Heat-shrink tube
1/2" x 1" (13mm x 25mm) |
| 2 Mastic strips | 1 Heat-shrink tube
5/16" x 1-1/2" (8mm x 38mm) |
| 2 Clamp ties | 1 Ground fault device with 120V
3-Prong NEMA 5-15 plug |
| 2 Crimp-on insulated terminals | |
| 1 Crimp-on non-insulated barrel | |
| 1 Heat-shrink tube
3/4" x 8" (19mm x 20cm) | |

Enough to complete:

One ground-fault protection power input power connection.

SLCBLKC: SLCBL End Seal Kit



Kit Contents:

- | | |
|--|--|
| 2 Heat-shrink caps | 2 Woven braid sleeves 1/2" x 4"
(13mm x 10cm) |
| 2 Heat-shrink tubes 3/4" x 5"
(19mm x 13cm) | |

Enough to complete:

Two end seal terminations.

SLCBLSK: SLCBL Splice and Tee Kit



Kit Contents:

- | | | |
|--------------------|--|---------------------------------|
| 1 Clamp tie | 1 Black heat-shrink tube
1" x 8" (25mm x 20cm) | 1 Heat-shrink tube |
| 3 Cable ties | 3 Black heat-shrink tubes
1/2" x 1" (13mm x 25mm) | 2 Crimp-on insulated terminals |
| 1 Cloth tape | 6 Black heat-shrink tubes
1/8" x 1" (3mm x 25mm) | 1 Crimp-on non-insulated barrel |
| 5 Mastic strips | | 1 End seal |
| 2 Heat-shrink caps | | |

Enough to complete:

One splice connection and one end seal termination or one tee connection and one end seal termination.

NOTE: This kit does not complete an input power connection.

SLCBL, SLMCBL, SLHCBL Connection / Termination Kits

For use in Hazardous Area Locations with SLCBL cable only (CSA approved).

For use in non-hazardous area locations with SLCBL, SLMCBL, SLHCBL cable (non-CSA approved).



Hazardous (Classified) Locations
Class I, Division 2, Groups A, B, C, D
Class II, Division 2, Groups E, F, G
Class III
-BP, -BF Series Only

Approvals valid only when used with appropriate heating cable and installation accessories, and installed in accordance with all applicable instructions, codes, and regulations.

PTBO-GET: SLCBL, SLMCBL, SLHCBL Power Connection Kit With Octagon Enclosure



Kit Contents:

- | | |
|--|--|
| 1 Octagon junction box with rail mounted DIN terminal block electrical connections | 1 Sealing gasket |
| 1 Pipe standoff mounting bracket | 1 M25x1.5 IP68 Seal fitting |
| 2 Pipe Straps | 2 Watertight sealing grommets |
| 1 Lock nut | 1 Watertight sealing plug |
| | 1 Green/Yellow heat-shrink tube 1/4" x 6" (6mm x 15cm) |
| | 2 Black heat-shrink tube 1/8" x 5-1/2" (3mm x 14cm) |

Enough to complete:

One input power connection.

JHE-GET: SLCBL, SLMCBL, SLHCBL Low-Profile End Seal Kit



Kit Contents:

- 1 End seal housing
- 1 Watertight sealing grommet
- 1 Pressure seal end with screws

Enough to complete:

One low-profile end seal termination.

JHS-GET: SLCBL, SLMCBL, SLHCBL Low-Profile Splice Connection Kit



Kit Contents:

- 1 In-line splice housing
- 2 Watertight sealing gaskets
- 2 Housing covers with screws
- 2 Watertight sealing grommets
- 2 Pressure seal ends with screws

Enough to complete:

One low-profile splice connection.

JHT-GET: SLCBL, SLMCBL, SLHCBL Low-Profile Tee Connection Kit



Kit Contents:

- 1 Tee splice housing
- 2 Watertight sealing gaskets
- 2 Housing covers with screws
- 3 Watertight sealing grommets
- 3 Pressure seal ends with screws

Enough to complete:

One low-profile tee connection.

NOTE: This kit does not complete an input power connection.