

3-Chip DLP™ Projectors

PT-RQ35K2 Series

Compact and Lightweight
30,500 lm 3-Chip DLP™
4K Projector Streamlines
Workflow Management



Note: Brightness measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. Maximum physical resolution 3840 x 2400 pixels with Quad Pixel Drive [ON] (PT-RQ35K2 only). Lens sold separately.

■ Main Features

01 | Revolutionize Projection with Streamlined Workflow

With high brightness and spectacular image quality, the light and compact PT-RQ35K2 Series projector eases the logistical burden with more efficient transport, installation, and storage. Save resources and enjoy greater convenience especially when backyard space is limited.

02 | Spellbinding Picture Quality

A combination of two blue and one red laser expands color-space reproduction over the PT-RQ32K. Vivid red and pure blue reproduction heightens realism for an immersive experience and takes high-resolution content to the next level.

03 | Original Cooling System for Projection Stability

Dedicated airflow path, cooling system, and finless radiator reinforce reliability. Dynamic Digital Control regulates red laser output and cooling for consistent image quality. Expect 20,000 hours¹ of maintenance-free projection with backup input² and laser failover circuitry offering peace of mind when projection can't be interrupted.

PT-RQ35K2 Series		
	PT-RQ35K2	PT-RZ34K2
Light Output	30,500 lm ³ / 30,500 lm (ANSI) ⁴ / 32,000 lm (Center) ⁵	
Resolution	4K (3840 x 2400 pixels) ⁶	WUXGA (1920 x 1200 pixels)



¹ Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment. ² Primary and backup terminal assignment is fixed. Input signals must be identical. ³ Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. ⁴ Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. ⁵ Average light-output value of all shipped products measured at center of screen in NORMAL Mode. ⁶ PT-RQ35K2 only. Maximum physical resolution 3840 x 2400 pixels with Quad Pixel Drive [ON]. ⁷ PT-RQ35K2 only. ⁸ Input signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ34K2. YPbPr 4:2:0 format only for 4K/60p and 4K/50p signals input via DIGITAL LINK. ⁹ PT-RZ34K2 only.

Streamlined Installation Workflow

Thanks to its uncommonly light and compact form factor, the PT-RQ35K2 Series can be transported and installed with two people. Setup on AC 100–120 V¹ minimizes delays while AC 200–240 V is rolled out on site. Preactivated upgrade kits for Geo Pro² expedite multi-screen adjustment. You can check content on PC screen prior to projection via Remote Preview, even while the projector is in Standby.

Spectacular Color for Multi-Screen Projection

Multi-laser light source (one red, two blue) dramatically enhances color reproduction. Optimized blue-laser wavelengths achieve truer blue while the red laser intensifies red expression for greater realism. Gradation Smoother³ removes color banding on the fly, while enhanced Black Level Correction ensures seamless blending on flat or curved screens.

¹ Japan/U.S. only. Brightness is limited to one-third of maximum when operating on AC 100–120 V power. ² Projector registration required. Visit [PASS](https://pass.panasonic.com) to register your projector and download free Geometry Manager Pro software for Windows*. ³ PT-RQ35K2 only. ⁴ Check device and OS compatibility at the App Store or the Google Play Store. ⁵ Projectors sold in some countries or regions require an ET-NUK10 Upgrade Kit available from [PASS](https://connect.panasonic.com) to activate NFC function. See NFC Regional Compatibility List for details. ⁶ Requires optional AJ-WM50 Series Wireless Module (sold separately). Product availability varies depending on country or region. ⁷ Some mobile devices do not support projector auto-focus function. ⁸ Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. ⁹ QUIET Mode: 46 dB, brightness limited to 20,000 lm. ¹⁰ Excluding lenses for PT-RQ50K.

Specifications

Model	PT-RQ35K2		PT-RZ34K2
Projector type	3-Chip DLP™ projector		
DLP™ chip	Panel size	24.4 mm (0.96 in) diagonal (16:10 aspect ratio)	
	Display method	DLP™ chip x 3, DLP™ projection system	
	Number of pixels	2,304,000 (1920 x 1200 pixels) x 3	
Light source	Laser diodes (Blue LD, Red LD)		
Light output ¹	30,500 lm ² / 30,500 lm (ANSI) ³ / 32,000 lm (Center) ⁴		
Time until light output declines to 50 % ⁵	20,000 hours (NORMAL), 24,000 hours (ECO), 26,000 hours (QUIET)		
Resolution	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)		WUXGA (1920 x 1200 pixels)
Contrast ratio ²	20,000:1 (Full On/Full Off, Dynamic Contrast [3])		
Screen size (diagonal)	1.78–25.4 m (70–1,000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95		
Center-to-corner zone ratio ²	90 %		
Lens	Optional (no lens included with this model)		
Lens shift ⁶ (From the origin point of the lens mounter)	Vertical	±55 % (+78 %, +68 % with ET-D75LE95, ±48 % with ET-D3LEW201/ET-D3LEW200, ±44 % with ET-D75LE6/ET-D3LEW60/ET-D3LEW300/ET-D3LEW600) (powered)	
	Horizontal	±20 % (±15 % with ET-D75LE6/ET-D3LEW60/ET-D3LEW300/ET-D3LEW600/ET-D3LEW201/ET-D3LEW200, ±12 % with ET-D75LE95, +25 %, 0 % with ET-D3LEU101/ET-D3LEU100) (powered)	
Keystone correction range	Vertical: ±45 ° (±40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LE20/ET-D3LE250, ±28 ° with ET-D75LE6/ET-D3LEW60/ET-D3LEW300/ET-D3LEW600, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW201/ET-D3LEW200, ±8 ° with ET-D3LEU101/ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60/ET-D3LEW300/ET-D3LEW600, ±5 ° with ET-D3LEU101/ET-D3LEU100/ET-D3LEW201/ET-D3LEW200, 0 ° with ET-D75LE95), When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.		
Terminals	SDI IN	—	
	HDMI™ IN	HDMI™ x 1 (Deep Color, compatible with HDCP 2.2, 4K/60p signal input ⁷)	
	DVI-D IN	—	
	MULTI PROJECTOR SYNC IN	BNC x 1	
	MULTI PROJECTOR SYNC OUT	BNC x 1	
	MULTI PROJECTOR SYNC IN terminal/ 3D SYNC 1 IN/OUT terminal (dual purpose)	—	
	MULTI PROJECTOR SYNC OUT terminal/ 3D SYNC2 OUT terminal (dual purpose)	—	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)	
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control	
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX, compatible with Art-Net, PLink™ (Class 2), Deep Color, HDCP 2.2, 4K/60p signal input ⁷	
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible	
	USB	USB connector (Type A) x 1 for optional Wireless Module (AJ-WM50 Series)/USB Memory Stick	
	DC OUT	USB Type A x 2 (for power supply, DC 5 V total of 2 A)	
Expansion slot	SLOT 1/SLOT 2 (total two terminals, vacant) for interface boards, SLOT NX compatible		SLOT (one terminal, vacant) for interface boards, SLOT NX compatible
Power supply	Single-phase AC 200 V–240 V (Light output will decrease when using the projector with AC 100 V to AC 120 V)		
Power consumption	2,550 W (2,570 VA) (Standby: 14 W)		2,450 W (2,470 VA) (Standby: 13 W)
On-mode power consumption (Operating mode)	NORMAL	2,480 W	
	ECO	1,960 W	
	QUIET	1,610 W	
Operation noise ²	49 dB (NORMAL), 46 dB (QUIET)		
Dimensions (W x H x D)	Approx. 598 x 353 x 780 mm (23 17/32" x 13 29/32" x 30 23/32") (not including protruding parts)		
Weight ⁸	69.8 kg (153.9 lbs)		68.6 kg (151.2 lbs)
Operating environment	Operating temperature: 0–45 °C (32–113 °F), operating humidity: 10–80 % (no condensation)		
Applicable software	Visual Software Suite, Geometry Manager Pro, Logo Transfer Software, Multi Monitoring & Control Software, Projector Network Setup Software, Smart Projector Control for iOS/Android™		

¹ When [OPERATING MODE] is set to [NORMAL]. ² Measurement, measuring conditions, and method of notation all comply with ISO/IEC 11118: 2020 international standards. Value is the average of all products when shipped. ³ Measurement, measuring conditions, and method of notation all comply with American National Standards Institute standards. Value is the average of all products when shipped. ⁴ Average light-output value of all shipped products measured at the center of the screen. ⁵ Around this time, light output will have decreased by approximately 50%. IEC62087: 2008 Broadcast Contents, NORMAL Mode, Dynamic Contrast [3], temperature 35 °C (95 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Estimated time until light output declines to 50 % varies depending on environment. ⁶ Lens shift is not supported on the ET-D3LEW50. ⁷ 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ34K2. ⁸ Average value. May differ depending on the actual unit. ⁹ When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).

Optional Accessories

• Optional Lenses

Fisheye Lens ET-D3LEF70¹

Fixed-Focus Lens ET-D75LE95 / ET-D3LEU101¹ / ET-D3LEU100¹ / ET-D3LEW50¹

Zoom Lens ET-D3LEW201¹ / ET-D3LEW200² / ET-D3LEW300² / ET-D3LEW60² / ET-D3LEW600² / ET-D75LE6 / ET-D3LEW10² / ET-D75LE10 / ET-D3LES20² / ET-D3LES250² / ET-D75LE20 / ET-D3LET30² / ET-D75LE30 / ET-D3LET40² / ET-D75LE40 / ET-D3LET80² / ET-D75LE8

¹ Equipped with Auto Lens Identification function.

² Equipped with Auto Lens Identification function and Stepping Motor.

• Stepping Motor Kit ET-D75MKS10

Note: Calibration is required each time the lens is mounted.

• Lens Fixed Attachment

ET-PLF10 (For ET-D3LEF70) / ET-PLF20 (For ET-D3LEU101/ET-D3LEU100/ET-D3LEW201/ET-D3LEW200)

Note: This attachment may be required in some installation environments.

• ET-FMP50 Series Media Processors

ET-FMP50 / ET-FMP20

Note: For more information, please visit <https://docs.connect.panasonic.com/projector/products/fmp50/>.

• Wireless Module AJ-WM50 Series

Note: Product availability may vary by country or region. Operating temperature: 0–40 °C (32–104 °F).

• NFC Upgrade Kit ET-NUK10

Note: Product availability may vary by country or region.

• High Frame Rate Upgrade Kit ET-SUK10

Note: For PT-RQ35K2 only.

• Real-Time Tracking Projection Mapping System ET-SWR10

Note: PT-RQ35K2 only. Conditions apply. Availability may vary by country or region. Visit <https://docs.connect.panasonic.com/projector/products/swr10> for more information.

■ Other Features

- Information Monitor shows temp., runtime, signal data, error codes
- Quiet Mode⁹ ideal for theaters, museums, planetariums
- Geometric Adjustment with Free Grid
- Multi-Screen Support System and Multi-Unit Brightness & Color Control
- Compatible with Panasonic 3-Chip DLP™ projection lenses¹⁰
- Supports various 3D signal inputs (PT-RZ34K2 only)
- Supports Multi Monitoring & Control Software



Scan QR Code to visit the Smart Projector Control webpage.

Smart Projector Control⁴ with NFC Function⁵

Get a head start on projector setup even without AC power: just pair your smartphone via NFC and enter Projector ID and IP address. Smart Projector Control app expedites network connection⁶ with a QR Code displayed on Information Monitor, no SSID or password required. Adjust settings without menu projection and focus via smartphone camera⁷.

Engineered for Absolute Reliability

Dynamic Digital Control precisely adjusts red-laser output to image requirements and temperature. Projection stability is maintained by a dedicated cooling system. Finless radiator boosts cooling efficiency while shielded laser drive preserves image quality over 20,000 hours⁸ of maintenance-free projection. Backup input and failover circuitry maintain image display in mission-critical situations.

Panasonic



For more information about Panasonic projectors, please visit:

Projector Global Website – <https://docs.connect.panasonic.com/projector/>

Facebook – www.facebook.com/panasonicprojectoranddisplay

YouTube – www.youtube.com/user/PanasonicProjector

LinkedIn – <https://www.linkedin.com/company/panasonic-projector-and-display/>

X – https://x.com/Panasonic_PND/

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade Dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. Trademark PLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Windows™ is either a registered trademark or Microsoft Corporation in the United States and/or other countries. Android is a trademark or registered trademark of Google LLC. iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. DisplayPort™ is a trademark owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. "Panasonic" is a registered trademark of Panasonic Holdings Corporation and is used under license from Panasonic Holdings Corporation. MEVIX and SOUND SHINE are trademarks or registered trademarks of Panasonic Projector & Display Corporation in Japan and other countries. All other trademarks are the property of their respective trademark owners. © Panasonic Projector & Display Corporation 2026.

All information included here is valid as of March 2026.

RQ35K2series_G2 Printed in Japan.