

Starling Tab-Tension CLR® Series


Ceiling Light Rejecting Motorized Projection Screen



Compatible with bottom placed Ultra-Short Throw Projectors ONLY

Product Description

The **Starling Tab-Tension CLR® Series** is a Ceiling Light Rejecting front projection screen for ultra-short throw projectors. Its tab-tension design assures a flat and taut projection surface for ripple-free images. The StarBright CLR® material absorbs overhead light to provide contrast-rich images that won't wash out. This is ideal for environments that require the lights being on such as boardrooms, training facilities or living/family rooms. Standard features include a wireless 12-volt trigger, IR/RF remote control package, and a detachable manual keypad switch.



Models	Diagonal	Aspect Ratio	View Width	View Height	Material	Gain	Case Color
ST101UH2-CLR	101"	16:9	87.2 in	49.0 in	StarBright CLR®	0.6	Black

For full list of models visit www.elitescreens.com

Product Features

- StarBright CLR® - Ceiling Light Rejecting front projection material absorbs up to 95% of overhead light
- Crafted for use with Ultra-short Throw (UST) tabletop/bottom mounted projectors
- Wide diffusion uniformity allows viewers to see a clear bright picture from any angle
- Multi-layer optical micro-structures filter out ambient light for superior image brightness and contrast
- Black absorbent layer improves black levels in bright and dark rooms
- Reflective layer concentrates projected light back to viewer's field of vision and negates light scatter
- Special lenticular surface provides superb color fidelity, contrast, and black/white dynamic range
- Available in 101" diagonal size in 16:9 format
- Black backing eliminates light penetration to avoid picture degradation
- Flush wall/ceiling mounts permit wood stud installation and allow screen to slide horizontally for proper centering
- Tab-tension design helps maintain a flat and taut projection surface
- Curved aluminum enamel black case is moisture resistant
- Includes handheld Infrared (IR) and Radio Frequency (RF) remote controls, and a wall box controller for manual on-wall operation.
- User-friendly programmable vertical drop position for easy installation
- Wall box controller is detachable for a clean look
- Built-in selectable channels allow one RF remote programming to control multiple screens and prevent interference
- 12v trigger feature allows the screen's UP/DOWN operation to synchronize with the projector's power cycle
- 2-Year / 3-Year ENR-G Manufacturer's Warranty by Elite Screens