

Display

Brightness (ANSI lumens)	4000
Resolution	4K UHD (3840×2160)
Native Aspect Ratio	16:9
Contrast Ratio (FOFO)	3,000,000:1
Display Color	30-bit (1.07 billion colors)
Light Source	Laser
Light Source Life	a. Normal 20000 hrs, b. ECO 30000 hrs

Optical

Throw Ratio	0.496
Zoom Ratio	Fixed
Lens	'F 2.8, f: 17.51 mm
Projection Offset (Full-Height)	114%
Keystone Adjustment	2D, (Auto) Vertical ± 30 degrees; Horizontal ± 30 degrees

Picture

Rec. 709 Coverage	93%
Picture Modes	Simulation, 3D, Bright, HDR10, HLG, Presentation, sRGB, User 1, User 2, Vivid

Compatibility

Input Lag	16.7 ms (1080P 60Hz)
Resolution Support	VGA (640 x 480) to 4K UHD (3840 x 2160)
Horizontal Frequency	15K~135KHz

Vertical Scan Rate	23~240Hz
--------------------	----------

I/O Interface

HDMI in	(x2), HDMI-1 (2.0b/HDCP2.2), HDMI-2 (2.0b/HDCP2.2)
LAN (RJ45)	(x1)
USB Type A	(x2)
RS232 in (DB-9pin)	(x1)

Audio

Speaker	15W, (x1)
Audio out (3.5mm Mini Jack)	(x1)

Environment

Operating Temperature	0~40°C
Power Supply	AC 100 to 240 V, 50/60 Hz
Typical Power Consumption (110V)	230W @110VAC
Stand-by Power Consumption	<0.5W
Network Stand-by Power Consumption	<2W
Acoustic Noise (Typ./Eco.)(dB)	30/24

Accessories

Remote Control w/ Battery	RCA011
Power Cord (by region)	x1 (1.8M)
Quick Start Guide	(x1) 22L
Warranty Card (by region)	Yes
Anti-dust Filter	(Optional)

Universal Ceiling Mount

CM00G3, (Optional)

Dimension & Weight

Dimensions (WxHxD) (mm)

279.2*120.5*229.3 (mm)

Net Weight (kg)

3.6 Kg+/- 100g

Dimensions (WxHxD) (inch)

10.99*4.74*9.03

Net Weight (lb)

7.93 lbs + 0.22 lbs

Projection System

Projection System

DLP