

RANGER

The Ranger is engineered to provide large volumes of water for use in irrigation and numerous other water system applications. Corrosion resistant design features, coupled with abrasion resistant components, ensure long, reliable life in the toughest environments.

- 4" NEMA Submersible
- 1 through 10 HP
- 25 through 80 GPM
- SST Suction and Discharge
- Heavy Wall Stainless Steel Shell



RANGER PUMP SELECTION TABLE

Cat. No.	Motor HP	GPM	Tank Pressure	Depth to Water																							
				0	20	40	60	80	100	120	140	160	180	200	250	300	350	400	450	500	550	600	650	700	750	800	850
SS10-25	1	25	20/40 30/50	35 30	31 27	27 22	22 17	18 12	11																		
SS10-35	1	35	20/40 30/50	37 25	25																						
SS15-25	1-1/2	25	20/40 30/50	36 33	33 30	30 27	27 23	23 20	20 15	15																	
SS15-35	1-1/2	35	20/40 30/50	49 42	43 34	35 26	28 15																				
SS15-50	1-1/2	50	20/40 30/50	65 55	56 45	46 34	37 20																				
SS20-25	2	25	20/40 30/50			38 36	36 33	33 31	31 27	28 24	25 20	21 16	17														
SS20-35	2	35	20/40 30/50		50 46	46 40	41 33	35 26	27 16																		
SS20-50	2	50	20/40 30/50	70 64	63 55	56 47	47 40	40 29	30																		
SS20-80	2	80	20/40 30/50	75 58	56 40	40																					
SS30-25	3	25	20/40 30/50							36 34	32	33 30	30 28	25 22	18 15												
SS30-35	3	35	20/40 30/50			49 45	46 42	42 37	38 33	33 26	27 21	15															
SS30-50	3	50	20/40 30/50	70	70 64	64 60	60 55	55 49	50 44	44 35	36 29																
SS30-80	3	80	20/40 30/50	93 81	81 71	72 60	60 48	50 37																			
SS50-25	5	25	20/40 30/50										38	37 36	34 33	31 30	28 27	25 24	22 21	18 16	13						
SS50-35	5	35	20/40 30/50							49	47	45	43	39	32	23	18										
SS50-50	5	50	20/40 30/50			72 70	70 66	67 64	64 60	61 57	57 54	54 50	51 46	41 36	30 23												
SS50-80	5	80	20/40 30/50	100	101 94	94 88	87 80	80 72	72 62	63 58	57 50	49 40	40														
SS75-25	7-1/2	25	20/40 30/50													39	37	36	34	32	30	28	26	23	19	16	
SS75-35	7-1/2	35	20/40 30/50											50 49	47 46	44 43	40 38	36 34	32 30	27 24	16						
SS75-50	7-1/2	50	20/40 30/50							70 67	67 65	65 63	60 58	55 53	49 46	43 40	35 32										
SS75-80	7-1/2	80	20/40 30/50		104	104 100	100 96	96 90	91 87	87 82	82 78	77 72	72 67	60 52	45 39												
SS100-35	10	35	20/40 30/50													51 49	49 48	48 47	46 45	43 42	40 39	38 37	35 34	32 30	29 27	25 23	
SS100-50	10	50	20/40 30/50											68 67	65 63	61 59	58 56	53 51	48 46	44 42	39 37	33 30					
SS100-80	10	80	20/40 30/50					104 101	97 95	95 93	93 90	89 86	84 81	72 70	68 65	58 55											