

Accessories

Piggyback Mechanical Float Switch



Applications

- Residential sewage waste transfer



Features

- RFSN-6, RFSN-9 and RFSN-10 convert any manual pump, up through 1/2 hp (115 V) or 1 hp (230 V)
- RFSN-16 and RFSN-20 convert any manual pump, up through 3/4 hp (115 V), or 2 hp (230 V)
- UL and CSA listing

Item #	Model	Volts	Max. Amps	Cord
599118	RFSN-6	115/230	13	10' 3 m
599117	RFSN-9	115/230	13	15' 4.6 m
599128	RFSN-9	208/230	13	15' 4.6 m
599210	RFSN-10	115/230	13	20' 6 m
599119	RFSN-10	115/230	13	25' 7.6 m
599211	RFSN-16	115/230	15	20' 6 m
599318	RFSN-20	125/250	20	20' 6 m (w/o plug)

Piggyback Vertical Mechanical Float Switch



Applications

- Residential sewage waste transfer

Features

- Converts any manual pump, up through 1/2 hp (115 V) or 1 hp (230 V)
- Adjustable pumping range from 6.5" (16.5 cm) to .75" (1.9 cm)
- Designed for use in confined areas
- Not sensitive to turbulence
- UL/CSA listing

Item #	Model	Volts	Max. Amps	Cord
599261	RVMS-10	115/230	13	10' 3 m
599262	RVMS-15	115/230	13	15' 4.6 m
599263	RVMS-20	115/230	13	20' 6 m

Piggyback Diaphragm Switch



Applications

- Converts manual pumps to automatic operation



Features

- RS-5 converts any manual pump, up through 1/2 hp (115 V)
- RS-5-LL (Low Level) converts any manual pump, up through 1/3 hp (115 V)
- UL and CSA listing (115 V models only)

Item #	Model	Volts	Max. Amps	Cord	Mounted to 5-MSP pump	
					On Level	Off Level
599008	RS-5	115	10	10' 3 m	6" - 9" 15.2 cm - 23 cm	1" - 4" 2.5 cm - 10.2 cm
599009	RS-5	115	10	18' 5.5 m		
599010	RS-5	230	10	8' 2.4 m (w/o plug)		
599014	RS-5LL	115	10	18' 5.5 m	2" - 3" 5 cm - 7.6 cm	1/2" - 1-1/2" 1.27 cm - 3.8 cm
599019	RS-5LL	115	10	25' 7.6 m		