




[Pumps](#) | [Compasses](#) | [Anchors](#) | [Winches](#) | [Electronics](#) | [Boat Care](#) | [News](#) | [Information](#) | [Site Map](#)



Model 17A General Purpose Pump

13.6v 12.0v

GPH @ Open Flow	3800	3192
GPH @ 3.35' feet in lift	3185	2670
GPH @ 6.7' feet in lift	2570	2157

FEATURES

- Fully Submersible
- Easy clean snap lock strainer
- Silent and vibrationless operation
- Anti-airlock protection
- Compact, efficient long life motor
- Ignition protected
- No burn-out when run dry
- Rust and Corrosion protection
- Used by leading boatbuilders worldwide
- marine grade blocked wiring

13.6v 12.0v

Amp Draw @ Open Flow	20.0	15.5
----------------------	------	------

ANSWERS TO FREQUENTLY ASKED QUESTIONS

- Not self priming; will not pull water up to itself
- Discharge hose must run continually upwards
- Reductions in hose size will reduce output
- Increases in hose size will not increase output
- Reversed polarity runs pump at 20% capacity
- Increase wire gauge for each add'l 20 foot run
- Check valves are not recommended
- Low pressure output (7-10 psi)
- Break in for 10 hours for maximum pumping
- Rule does not repair pumps - it is not cost efficient for the consumer
- Rule does not sell pump parts due to liability

Specification

Fuse Size	25 amps
Discharge Opening	1-1/2"
Inlet Opening	1-1/2"
Rule Hose	Model 88 or 84
Rule Thru-Hull Fitting	59
Housing Material	Acetal
Strainer Material	Acetal
Impeller Material	Nylon
Shaft Material	Stainless
Seal Material	Nitril/Teflon
Temperature Limit	200 F
Fluid Capabilities	Bilge Water
Typical Life	2500 hours
Wire Length	29"
Wire Gauge	14 gauge
Weight	5 lb 10 oz
Height	5-1/4"
Width	8-1/2"
Depth	6-1/2"

CERTIFICATIONS

- NMMA Type Accepted Equipment # 704176
- IMCI Certified - ISO 8849
- CE Certified
- UPC Code 0-42237-08338-8