



[Members](#) |
 [Home](#) |
 [Company Profile](#) |
 [Product Information](#) |
 [Customer Service](#) |
 [Events / News](#) |
 [Site Map](#)

For Trade Accounts Only
Please login to enter or
check on your order

[CLICK HERE](#)

JABSCO
Marine and Industrial
Pumps and Accessories

rule
Submersible Bilge Pumps
and Marine Accessories

FLOJET
Industrial, RV, Marine
and Beverage Products

DANFORTH
Compressors

SUDBURY
Boat Care Products



Model 27D 1100 Gallons Per Hour

	13.6v	12.0v
GPH @ Open Flow	1100	1050
GPH @ 3.35' feet in lift	860	720
GPH @ 6.7' feet in lift	600	480

	13.6v	12.0v
Amp Draw @ Open Flow	5.0	3.3

FEATURES

- Fully Submersible
- Easy clean snap lock strainer
- Silent and vibrationless operation
- Anti-airlock protection
- Compact, efficient long life motor
- Ignition protected
- No burn-out when run dry
- Rust and Corrosion protection
- Used by leading boatbuilders worldwide
- marine grade blocked wiring

ANSWERS TO FREQUENTLY ASKED QUESTIONS

- Not self priming; will not pull water up to itself
- Discharge hose must run continually upwards
- Reductions in hose size will reduce output
- Increases in hose size will not increase output
- Reversed polarity runs pump at 20% capacity
- Increase wire gauge for each add'l 20 foot run
- Check valves are not recommended
- Install a vented loop for anti-siphoning
- Break in for 10 hours for maximum pumping
- Rule does not repair pumps - it is not cost efficient for the consumer
- Rule does not sell pump parts due to liability

CERTIFICATIONS

- NMMA Type Accepted Equipment # 704203
- IMCI Certified - ISO 8849
- CE Certified
- UPC Code 0-42237-08345-6

Specification

Fuse Size	6 amps
Discharge Opening	1-1/8"
Discharge Finish	Barbed
Rule Hose	Model 80 or 83
Rule Thru-Hull Fitting	Model 60
Housing Material	ABS
Strainer Material	ABS
Impeller Material	Nylon
Shaft Material	Stainless
Seal Material	Nitril/Teflon
Temperature Limit	200 F
Fluid Capabilities	Bilge Water
Typical Life	1500 hours
Wire Length	29"
Wire Gauge	16 gauge
Weight	10 oz
Height	4-1/4"
Width	2-3/8"
Depth	2-3/8"
Strainer Replacement	M 275