

1U 19" Widescreen LCD KVM Drawer















Features & Benefits

- ▶ 1U console, server rack mounted, with universal tapped rails (square hole)
- 19" Widescreen Samsung LED LCD with Hi-Resolution (1440 x 900)
- Green LED-backlit panel technology
- High modular scalability for customized build: KVM Switch, Peripherals & More
- Combo interface with PS/2 or USB input with front USB port access
- New molded front handle for easy maneuver, and two point lock system
- 6 foot Combo KVM cable included

Modular Scalability

- Multi-platform switch capability with any Raloy PS/2, USB or Sun KVM
- Mouse: Touchpad(e) or Trackball(b)
- Keyboard available in 13 languages
- VGA Broadcast-grade input
- S-Video + Composite (BNC) or Audio input
- HDMI or DVI-D
- DC power: 48V, 24V or 12V



RW119-N-101













VGA

S-Video + BNC


Audio


HDMI

DVI

DC Power









Keyboard Options











Specifications (Single console)

Weight

25 lbs (11.5 kgs) Net: Gross: 44 lbs (20 kgs)

LCD Panel

Casing Color:

SAMSUNG Grade A Manufacturer: Size (diagonal): 19" widescreen TFT

Max resolution: 1440 x 900

Brightness (cd/m2): 250 Backlight: LED 16.7M Colors: Contrast ratio (typ): 1000:1 Viewing angle (H/V): 160° x 160° Active area (mm): 408 x 255 MTBF (hrs): 30.000 Signal input: **VGA**

Black (RAL 9005)

• Dimensions Product:

17.4W x 23.6D x 1.73H in. (442 x 600 x 44 mm.) Packing: 23.2 x 33.9 x 5.5 in. (590 x 860 x 140 mm.) Mounting Depth: 24 in. (min) to 32.5 in. (max) (609.9 to 825.5 mm.)

Environmental

Operating: 32 to 122°F (0 to 50°C) Degree Storage: 23 to 140°F (-5 to 60°C) Degree

Relative humidity: 5~90%, non-condensing

10G acceleration (11 ms duration) Shock: Vibration: 5~500Hz 1G RMS random vibration

Regulatory

Safety: cUL, FCC & CE certified Environmental RoHS2 & REACH compliant

Power

Input: Auto-sensing 100 to 240VAC, 50 / 60Hz

Max. 48 Watt, Standby 5 Watt Consumption:

VGA + USB or PS/2, server end Combo KVM Cable:

DB15 (VGA, USB KB & MS), console port







REACH

1 (866) 395-5927 www.raloy.com