

Portable Scene Light Rechargeable Lantern



Material/ Lens High-impact thermoplastic housing. Weatherproof construction; O-ring sealed, unbreakable polycarbonate with scratch-resistant coating

Dims/Weight Length: 22 in. (55.88 cm) Body Width: 6.5 in. (16.5 cm) Overall Height: 11 in. (27.9 cm) Head Diameter: 6.7 in. (17 cm)
(Retracted Position) 25 lbs (11.3 kg) with batteries

Light Source Six C4® LEDs and wide pattern reflectors produce a uniform flood pattern with two selectable beam widths and three light output intensities:
 - High for a super-bright flood beam: 5,300 lumens; 410m beam; runs 4 hours
 - Medium for an intense beam and longer run time: 2,500 lumens; 292m beam; runs 9 hours
 - Low for when a less intense beam is ideal and for longer run time: 1,300 lumens; 215m beam; runs 18 hours

Switch Toggle switch allows operation from internal battery or continuous operation from external 12V DC power source

Battery Two zero-maintenance 12V, 7.2Ah (total 14.4 Ah) sealed lead acid batteries are rechargeable up to 500 times

Charging Red and green LEDs provide charge status feedback. 10 Hour charge to 90% battery capacity with continuous trickle charge to maximize battery capacity. Batteries will continue to charge while operating directly from an external 12V DC power source when using the remote cord. AC charger also included for continued use

- Features**
- Selectable diffuser settings for two beam widths. Works with all three modes
 - Optimum peripheral illumination for scene lighting; 90° swivel to aim the beam where you need it for task lighting
 - Balanced design and easy setup:
 - Less than 30 seconds for full deployment
 - Pole extends to 72"; cord built into the pole to avoid snags
 - Stabilization legs provide balance on uneven surfaces
 - Packs to a compact size (22"; 55.88cm) for easy stowage
 - IP67 rated; dust-tight and waterproof to 1 meter for 30 minutes
 - Designed to resist 40mph wind continuous in all directions with head fully extended

Approvals Most models meet applicable European Community Directives

Warranty Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction.



Selectable diffuser settings for two beam widths
Works with all three modes

Item Description	UPC	Item #
Portable Scene Light with 120V AC/12V DC - Yellow	080926-45670-9	45670
Portable Scene Light with 230V AC/12V DC - Yellow	080926-45671-6	45671
Portable Scene Light with 240V AC/12V DC - Yellow	080926-45672-3	45672
Portable Scene Light with 240V (AUS/NZ) AC/12V DC - Yellow	080926-45674-7	45674
Portable Scene Light with 100V AC/12V DC - Yellow	080926-45673-0	45673

Assembled in USA



22063
Power Supply



22064
120V



22063
230V



22066
UK 240V



22067
100V



22068
Aus/NZ 240V



45630



44050

Item	UPC	Item #
12V DC power cord 10ft (3 meters)*	080926-22056-0	22056
Portable Scene Light Power Supply	080926-22063-8	22063
Portable Scene Light Cord with 100V AC Plug - Works with Portable Scene Light power supply (22063)*	080926-22067-6	22067
Portable Scene Light Cord with 120V AC Plug - Works with Portable Scene Light power supply (22063)	080926-22064-5	22064
Portable Scene Light Cord with 230V AC Plug - Works with Portable Scene Light power supply (22063)	080926-22065-2	22065
Portable Scene Light Cord with 240V AC Plug - Works with Portable Scene Light power supply (22063)	080926-22066-9	22066
Quick Release Strap	080926-44050-0	44050
Shoulder Strap *	080926-45232-9	45232
Battery - HID LiteBox/E-Flood LiteBox HL/Portable Scene Light	080926-45630-3	45630

*Image not shown



STREAMLIGHT



30 Eagleville Road • Eagleville, PA 19403 • 610-631-0600/800-523-7488 Phone • 610-631-0712/800-220-7007 Fax
www.streamlight.com Portable Scene Light 3/16