

PRODUCT FACT SHEET

CLIPMATE® USB

LITHIUM POLYMER RECHARGEABLE FLASHLIGHT

MARKET

APPLICATIONS: Professional Light - Hardware/Tool, Industrial, Law Enforcement, Security, Automotive,

Sporting Goods, Consumer.

DESCRIPTION: The Clipmate® USB is a sleek compact USB rechargeable, lithium polymer battery powered

flashlight with a flexible neck designed to put light where you need it. The light is robust in design for use in all markets. It features a multi function switch, a pocket clip for convenience, and amazing brightness and run time for a light of its size. With its built in USB charge tab, there is no need for a cord to recharge the light. Its polymer housing makes the light extremely durable,

abrasion resistant and light weight. Available in Black.

CASE MATERIAL: Polycarbonate + Polyester

DIMENSIONS: Length: 3.20 in. (81 mm) Width: 1.39 in. (35 mm) Thickness: .65 in. (17 mm)

WEIGHT: 1.9 oz (53.8 grams) with battery.

LENS: Polycarbonate lens; gasket sealed.

LIGHT SOURCE: White: C4 LED technology, impervious to shock with a 30,000 hour lifetime.

Red: 3 mm LED: 620-630 nm

LIGHT OUTPUT:



C4® White LED - High = 500 candela peak beam intensity, 44 meter beam distance and 70 lumens measured system output. 3mm Red LED High = 0.5 lumens measured system output. Fully regulated output for consistent lumen performance over the battery life. (See chart for low outputs.)

ON/OFF: Push button switch - cycle through low, high and off. Turn light on, then press and hold the button

for 2.5 seconds for the light source to change from white LED to red LED to preserve your night vision. NOTE - The light will remain on the selected light source until you press and hold the button

to change the LED light source.

RUN TIME:



3.5 hours of run time. All runtime claims are to 10% of initial lumen output.

BATTERY: Streamlight Lithium Polymer cell with on board safety circuit. Rechargeable up to 300 times.

CHARGING: Digital control circuit that prevents overcharge.

Fully recharges battery in 2.5 hours and charges battery in product.

Charge indication LED: LED Red - Charging; LED Blinking Red - Charged. (The red LED in the lights

head is used for charge indication.)

FEATURES: C4® LED technology for extreme brightness.

IPX4 rated for water resistant operation. All openings sealed.

1 meter impact resistance tested.

USB rechargeable via the tethered USB cover.


APPROVALS: (Meets applicable European Community Directives.

WARRANTY: Streamlight's Limited Lifetime Warranty

OPTIONAL

ACCESSORIES: USB/AC adaptor(s).

FL1 STANDARD	WHITE LOW	WHITE HIGH	RED LOW	RED HIGH
315	10 LUMENS	70 LUMENS	.2 LUMENS	.5 LUMENS
0	24h	3h 30m	65h	16h
M	14m	44m	3m	6m
	50cd	500cd	3cd	9cd



All performance claims to ANSI/NEMA FL1-2009 Standard

Issued: 12/19/2013 Revised: 12/23/2013