STREMULIGHT

PRODUCT FACT SHEET

ProTac HL® HEADLAMP HIGH LUMEN LITHIUM HEADLAMP

MARKET

APPLICATIONS: Sporting Goods, Consumer, Industrial, Law Enforcement, Security, Emergency Medical Services,

Hardware/Tool

DESCRIPTION: With 635 lumens of blinding light, the ProTac HL® Headlamp is the brightest addition to the

headlamp series. The ProTac HL® Headlamp offers the latest in power LED technology and three different user selectable programs. The combination of small size and output from the C4® LED result in one of the brightest headlights for its' size. Packaged with an elastic headband and a

rubber headband for helmet mounting.

CASE MATERIAL: 6000 series machined aircraft aluminum with anodized finish. Available in Black.

DIMENSIONS: Facecap Diameter: 1.20 in. (3.05 cm) Width: 3.66 in. (2.54 cm)

Maximum Depth (including headband mounting plate): 2.60 in. (6.60 cm)

WEIGHT: 6.6 oz (187 grams) with batteries (included with purchase).

LENS: Glass lens, gasket sealed.

LIGHT SOURCE: C4® LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provides regulated intensity.

FL1 STANDARD FL1 STANDARD FL1 STANDARD FL1 STANDARD

ON/OFF: Multi-function, push-button switch. One handed operation of momentary or variable intensity.

TEN-TAP™ programmable switch allows user selection of one of three different programs:

high/medium/low (factory default), high only, or low/medium/high.

RUN TIME: See chart. All claims to 10% of initial lumen output.

BATTERY: Two (2) 3 Volt CR123A Lithium batteries. CR123A batteries have a shelf life of 10 years.

FEATURES: C4[®] LED technology for extreme brightness.

IPX4 rated for water resistant operation. All openings o-ring sealed.

1 meter impact resistance tested.

LED Solid State Power Regulation provides maximum light output throughout battery life. TEN-TAP™ programmable switch allows user to select one of three different programs.

Serialized for positive identification.


WARRANTY: Streamlight's Limited Lifetime Warranty

APPROVALS: Meets applicable European Community directives. **CE**

OPTIONAL

ACCESSORIES: N/A

i	FL1 STANDARD	HIGH	MEDIUM	LOW
OUTPUT	31/5	635 LUMENS	105 LUMENS	20 LUMENS
RUNTIME	0	1h 45min	8h	36h
DISTANCE		184m	76m	33m
INTENSITY		8,500 cd	1,450 cd	280 cd



All performance claims tested to ANSI/NEMA FL1-2009 Standard

Issued: 08/15/2013

Revised: 04/15/2015 Rev: 3 Made In China Document #169