

## TLR-2°IRW

## RAIL-MOUNTED TACTICAL LIGHT WITH INTEGRATED IR AIMING LASER

## The TLR-2 IRW features a Class 1 "Eye Safe" IR laser and 300 lumens of visible, blinding white light.

One handed snap-on and tighten interface keeps hands away from muzzle when attaching/detaching

Visible white C4® LED

when attaching/detaching

Windage a brass bush

850nm IR laser Class 1 "Eye Safe" Ambidextrous momentary/steady
On-Off switch

Double tap momentary paddle to activate strobe

Three-position mode selector switch (White LED only, Safe Off, IR Laser only)

Windage and elevation adjustment screws mounted in brass bushings; dependable zero retention

Highly accurate sight repeatability when remounting

C4 LED delivers 12,000 candela peak beam intensity; 300 lumens IR Laser: Class 1; eye safe output power less than 0.8mW

Deep-dish parabolic reflector produces a concentrated beam of white light with optimum peripheral illumination

IR Laser provides long-range targeting

Runs 2.5 hours (White LED only) IR Laser only function runs 45+ hours

Solid-state current regulation for consistent illumination level

Mounts directly to handguns with Glock-style rails and to all MIL-STD-1913 (Picatinny) rails

Securely fits a broad range of weapons; Includes keys for Glock-style, Picatinny, Beretta 90two, S&W 99 and S&W TSW

6000 series machined aircraft aluminum with anodized finish with high-impact, chemically resistant polymer laser housing

Borofloat high temperature glass lens

Operating temperature: -40°F to +140°F

IPX4 water-resistant

User programmable strobe can be enabled/disabled

Powered by two 3V CR123A lithium batteries (included)

Tethered battery door and latch mechanism prevents battery door loss while providing easy battery replacement

Serialized for positive identification

3.39 in. (8.61 cm); 4.72 oz (133.8 grams)

Limited lifetime warranty

Visit www.streamlight.com for full warranty information

69165 - TLR-2 IRW with lithium batteries



