

POLYTAC® 90 LED LITHIUM POWER RIGHT ANGLE POLYMER FLASHLIGHT

MARKET: Fire & Rescue, Sporting Goods, Law Enforcement, Security, Hardware/Tool, Industrial, Consumer

DESCRIPTION: The PolyTac® 90 LED is a super bright and compact right angle personal light with C4®LED technology. This light offers microprocessor controlled high and low intensity modes, strobe mode and integrated carabiner style D-ring for a variety of attachment methods. Operates on CR123A Lithium primary cells.

CASE MATERIAL: High impact super tough nylon polymer for exceptional durability and sure grip. All openings o-ring sealed for water resistance. Available in black and yellow.

DIMENSIONS: Height: 5.22 in. (13.3 cm) Head Diameter: 1.25 in. (3.18 cm) Body Diameter: 1.00 in. (2.54 cm)

WEIGHT: 4.1 oz (116 grams) with batteries (included in purchase)

LENS: Tempered glass lens, gasket sealed.

LIGHT SOURCE: C4®LED technology, impervious to shock with a 50,000 hour lifetime.

LIGHT OUTPUT: See chart. Optimized electronics provide regulated intensity. Textured parabolic reflector produces a smooth beam hotspot with optimum peripheral illumination to aid in navigation.



RUN TIME: See chart. All claims to 10% of initial lumen output. Strobe: 6 continuous hours.



ON/OFF/MODE: Head mounted push button switch provides one handed momentary or constant "on" operation. Fast double click from "off" to activate Strobe mode; fast triple click from "off" to activate Low mode.

BATTERIES: Two (2) 3 Volt CR123A Lithium batteries with a shelf life of 10 years.

FEATURES: C4®LED technology for extreme brightness. 90 degree head.







1 meter impact resistance tested.
IPX7 rated design; waterproof to 1 meter for 30 minutes.
Integrated carabiner style D-ring for a variety of attachment methods.
Fully rotatable/reversible/removable clip to allow a variety of mounting positions.
LED Solid State Power Regulation provides maximum light output throughout battery life.
Individually serialized for positive identification.

APPROVALS: Meets applicable European Community Directives. 
Meets requirements of NFPA 1971-8.6 (2007).

WARRANTY: Streamlight warrants this product to be free of defect, including the LED, for a lifetime of use. We will repair, replace or refund the purchase price, at our option, of any Streamlight product that does not work as a result of a manufacturing defect for as long as you own it. This limited lifetime warranty excludes abuse, batteries, switches and electronics. Switches and electronics have a two (2) year warranty with proof of purchase.

OPTIONAL ACCESSORIES: N/A

	FL 1 STANDARD	HIGH	LOW
OUTPUT		170 LUMENS	17 LUMENS
RUNTIME		3h 45min	30h
DISTANCE		167m	53m
INTENSITY		7,000cd	700cd

