

SIDEWINDER COMPACT® II

MULTI-BATTERY MULTI-SOURCE HANDS-FREE FLASHLIGHT

FL 1 STANDARD	C4 LED w/ CR123 HIGH	C4 LED w/ AA LITHIUM HIGH	C4 LED w/ AA ALKALINE HIGH
	55 LUMENS	47 LUMENS	47 LUMENS
	6h	6h	2h
	69 m	63 m	63 m
	1175 cd	1000 cd	1000 cd



Description: Ultra-compact, high performance, multi-battery, multi-source LED flashlight with C4® LED technology. This flashlight has been engineered to meet a variety of hands free task illumination requirements with various color LEDs operable at varying outputs and runtimes. The flashlight features a 185 degree tilting body and belt or web clip to allow positioning of the illumination source at the work area.

Case Material: High impact super tough nylon case offers exceptional durability and weather resistance. All openings are O-ring sealed

Dims/Weight: Length: 3.00 in. (7.62 cm) Width: 1.07 in. (2.72 cm) Depth: 2.04 in. (5.21 cm)
 2.4 ounces (68 grams) with CR123A lithium battery (included with purchase).
 3.3 ounces (94 grams) with CR123A lithium battery and optional helmet mount

Light Source/output: White C4 LED w/CR123: 55 lumens, 1,175 candela peak beam intensity and 69m beam distance
 White C4 LED w/AA: 47 lumens, 1,000 candela peak beam intensity and 63m beam distance
 5mm IR LED: 25mW/sr (min) radiant intensity
 5mm Red LED: 1.5 lumen, 60 candela peak beam intensity and 15m beam distance
 5mm Blue LED: 1.8 lumens, 130 candela peak beam intensity and 23m beam distance
 Illumination output electronically regulated. (See model for specific LED configuration)

On/Off/Intensity Mode Selection: Compound On-Off mode selector switch ergonomically separates On-Off-Dimming-Strobe and LED selection functions. Design does not require the operator to access separate switching locations on the device. Rubber dome actuator and 4 position pull-to-turn locking rotary selector knob with IR LED tactile indicator provides easy operation even when wearing heavy gloves.

<u>CR123 / AA Lithium Battery</u> LED Type	Low (10% Output)	Medium 1 (25% Output)	Medium 2 (45% Output)	High (100% Output)	Strobe (100% Output)
White C4®	70 Hours	28 Hours	16 Hours	6 Hours	10 Hours
5mm IR or Red	100+ Hours	72 Hours	36 Hours	16 Hours	24 Hours
5mm Blue or Green	100+ Hours	60 Hours	24 Hours	12 Hours	18 Hours

<u>AA Alkaline Battery</u> LED Type	Low (10% Output)	Medium 1 (25% Output)	Medium 2 (45% Output)	High (100% Output)	Strobe (100% Output)
White C4®	40 Hours	16 Hours	8 Hours	2 Hours	4 Hours
5mm IR or Red	100+ Hours	48 Hours	18 Hours	9 Hours	14 Hours
5mm Blue or Green	100+ Hours	36 Hours	12 Hours	6 Hours	10 Hours

Battery: One (1) CR123A size lithium cell, AA size alkaline cell or AA size lithium cell cell. Lithium cells allow operation in extreme temperature environments (-40F to 140F)

Approvals: Meets applicable European Community Directives

Warranty: Streamlight warrants its Sidewinder Compact (excepting batteries) will be free from manufacturing defects under normal use for 12 months after purchase. During the warranty period, at its sole discretion, Streamlight will repair or replace any defective part or product.

Features:	Push button switch specified to 300K operations	3 meter multiple orientation impact resistance tested
	Pull-to-turn locking rotary knob prevents accidental mode changes	Cord attachment holes provided in battery compartment cover capable of supporting 25 lbs of load
	Push button switch enables/disables selected illumination source starting at low output and progressing to the brightest output in 4 discrete steps (Sportsman's model enables selected illumination source starting at high output and progressing to the dimmest output). Double click of push button initiates high output strobe of selected illumination source.	Tactile battery polarity indicators for battery replacement in the dark. Built in battery polarity protection guards against damage to the light
		IPX7 Rated design; waterproof to 1 meter for 30 minutes. O-Ring and gasket sealed openings. Meets MIL-STD-810F, Method 512.4.



Item		UPC	Part #
Military Model High Performance multi-source LED flashlight. Each LED features 4 levels of increased output intensities: Low, Medium, Medium-High, High, plus Strobe.			
Sidewinder Compact II Military: 4 LEDs feature 4 levels of increasing output intensities: Low, Medium, Medium-High, High plus Strobe . Includes CR123A battery and helmet mount. Boxed.		080926-14510-8	14510
Sidewinder Compact II Military: 4 LEDs feature 4 levels of increasing output intensities: Low, Medium, Medium-High, High plus Strobe . Includes CR123A battery, helmet mount and elastic headstra. Clam packaged		080926-14512-2	14512
Sidewinder Compact II Military: 4 LEDs feature 4 levels of increasing output intensities: Low, Medium, Medium-High, High plus Strobe . Includes CR123A battery, helmet mount and elastic headstrap. Boxed		080926-14514-6	14514
Sidewinder Helmet Mount	Coyote	080926-14055-4	14055
Sidewinder Helmet Mount	Green	080926-14056-1	14056
Safety Wand	Glow in the Dark	080926-14902-1	14902
1913 rail mount adapter (for helmets)	Coyote	080926-14057-8	14057
1913 rail mount adapter (for helmets)	Green	080926-14058-5	14055
Sidewinder Compact head strap	Coyote	080926-14059-2	14059
Lithium batteries (2) Pack		080926-85175-7	85175
Lithium batteries (12) Pack		080926-85177-1	85177
Lithium batteries (400) Pack		080926-85179-5	85179
Lithium batteries (6) Pack		080926-85180-1	85180

