



***Composite and S-Video to Composite and
S-Video Converter***

***Part Number: CSV2CSVD -
74-111-604***

Product Description:

This product will work with either NTSC or PAL video formats. the converter provides the following functions:

When powered up with video from both an S-Video (Y/C) and composite source, the converter will output the S-Video (Y/C) source to both the S-Video (Y/C) and composite outputs.

If the S-Video (Y/C) video source fails, the converter will output the composite source to both the S-Video (Y/C) and composite outputs.

If the converter is outputting from the composite source and the S-Video (Y/C) video source comes back online, the converter will continue to output the composite source until the converter is power cycled.

The converter is not intended to be used to convert NTSC to PAL or PAL to NTSC. The converter outputs NTSC if the input source is NTSC, and outputs PAL if the input source is PAL.

Installation:

Plug the wall transformer into a powered outlet. Plug the power plug into the converter, the green power LED should come ON.

SViDEO.COM
22136 Westheimer Pkwy 421
Katy TX 77450
956-566-420

Overall Specifications

Video Specifications

Signal Input Format	NTSC or PAL	480i/576i
Input Impedance	75 Ohms	
Signal Output Format	S-video (Y/C) and Composite Video	
Output Impedance	75 Ohms	
Input Signal Range	1Vpp input	
Input Connectors	RCA(Yellow-composite), S-Video (female 4-pin mini DIN)	
Output Connectors	RCA(Yellow-composite), S-Video (female 4-pin mini DIN)	

General Specs

Power Voltage	9V DC
Power Status	Green LED
Power Current	<200mA
Temperature	-40C to +80C -40F to +176F
Humidity	2-98%
Weight	0.5 lb.

