



## HY-PRO-HP438L625MB

| Product Attribute                   | Specifications   |
|-------------------------------------|--|
| Filter Type:                        | Hydraulic Filter Cartridge   |
| Media Type:                         | Pleated Microglass Media<br>(Available in Stainless Mesh or Pleated Paper Media – SEE CHART BELOW) |
| Overall Height:                     | 6.26"  |
| Outer Diameter:                     | 3.90"  |
| Inside Diameter - Top:              | 1.93"  |
| Inside Diameter - Bottom:           | 2.07"  |
| Collapse Pressure:                  | 435 PSI  |
| Operating Temperature:              | -13° to 248°F  |
| Filter Area:                        | 3.08 Square Feet   |
| Direction of Flow:                  | OUTSIDE-IN   |
| Seal Material:                      | BUNA   |
| Micron Rating:                      | 20   |
|                                     |  |
| MEDIA Available                     | Micron Ratings available   |
| Pleated Microglass Media            | 3-micron, 5µm, 10µm, 20µm, 40µm  |
| Pleated Paper Media                 | 25-micron  |
| 304 Stainless Steel Wire Mesh Media | 10-micron Stainless Steel, 25SS, 40SS, 60SS, 100SS   |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.