



Millennium-Filters.com  
 QUALITY OEM REPLACEMENT FILTERS



## HY-PRO HP83L1625MV

| Product Attribute      | Specifications   |
|------------------------|--|
| Filter Type:           | Hydraulic Filter Cartridge   |
| Media Type:            | Pleated Microglass Media   |
| Overall Height:        | 16.84"   |
| OD:                    | 5.98"  |
| ID:                    | 4.14"  |
| Collapse Pressure:     | 145 PSI (also available in High Collapse version rated up to 3045 PSI) |
| Operating Temperature: | -13° to 250°F  |
| Filter Area:           | 15.57 sq.ft.   |
| Direction of Flow:     | Outside-In   |
| Seal Material:         | Viton  |
| Micron Rating:         | 25   |
| Beta Ratio:            | 200/25   |
| Efficiency:            | 99.5%  |

| MEDIA Available                             | Micron Ratings available  |
|---|---|
| Pleated Microglass Media                    | 1-micron, 3µm, 6µm, 10µm, 25µm                                    |
| Pleated Paper Media                         | 10µm, 25µm  |
| Stainless Steel Wire Mesh Media<br>(304 SS) | 10-micron, 25µm, 60µm, 80µm,<br>100µm, 125µm, 150µm, 200µm, 420µm |

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.