

Millennium Filters.com QUALITY OF REPLACEMENT FILTERS



PARKER 934568

10μm, 3 bar bypass (BPVS)

Product Attribute	Specifications
Filter Type:	Hydraulic Filter Cartridge
Media Type:	Pleated Microglass Media
Overall Height:	10.83"
Outer Diameter:	3.78"
Inside Diameter - Bottom:	1.90"
BPVS* Setting:	3.00 bar
Collapse Pressure:	435 PSI
Operating Temperature:	-13° to 250°F
Filter Area:	6.90 Square Feet
Direction of Flow:	OUTSIDE – IN
Seal Material:	VITON
Micron Rating:	10
Beta Ratio:	200/10
BPVS* Setting:	3.00 bar

^{*} The standard unit is equipped with an integral bypass valve that is built into the closed end cap allowing fluid to flow when the pressure reaches the set level to avoid system shutdown. Elements should be changed to prevent buildup of contaminants in the system. Bypass valve settings are 1-bar, 3-bar and 6-bar.

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.

<u>www.Millennium-Filters.com</u> 24855 NOVI ROAD Suite 105 NOVI, MICHIGAN 48375 Phone: 248-719-7441 Fax: 248-869-6090