



Millennium-Filters.com
QUALITY OEM REPLACEMENT FILTERS



SWIFT-SF3313620UMV

Product Attribute	Specifications
Filter Type:	Hydraulic Filter Cartridge
Media Type:	Pleated Microglass (see chart below)
Overall Height:	9.61"
OD:	2.36"
ID:	0.99"
Collapse Pressure:	305 PSI (3045 PSI High Collapse models available)
Operating Temperature:	-13° to 250°F
Filter Area:	2.66 SQ.FT.
Direction of Flow:	Outside-In
Seal Material:	Viton
Micron Rating:	20 (see options below)
Beta Ratio:	200/20
Efficiency:	99.5%
MEDIA Available	Micron Ratings available
Pleated Microglass Media GW = Glass + Water Removal Media	3-micron, 6µm, 10µm, 25µm, 40µm 3GW, 6GW, 10GW, 25GW
Pleated Paper Media PW = Paper + Water Removal Media	3-micron, 10µm, 25µm 10PW, 25PW
Stainless Steel Wire Mesh Media (304 SS)	10-micron, 25µm, 40µm, 74µm, 100µm, 149µm, 250µm

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.