

Millennium Filters.com QUALITY OEM REPLACEMENT FILTERS



VICKERS (EATON) V0332RB2C10

10μm, 3 bar bypass (BPVS)

TICKERS (EATON)	TOSSILLE	10pm/ 5 bar bypass (51 15)
Product Attribute		Specifications
Filter Type:		Hydraulic Filter Cartridge
Media Type:		Pleated Microglass Media
Overall Height:		7.64"
Outer Diameter:		3.78"
Inside Diameter - Bottom:		1.90"
BPVS* Setting:		3.00 bar
Collapse Pressure:		365 PSI
Operating Temperature:		-13° to 250°F
Filter Area:		4.60 Square Feet
Direction of Flow:		OUTSIDE – IN
Seal Material:		VITON
Micron Rating:		10
Beta Ratio:		200/13
BPVS* Setting:		3.00 bar

^{*} The standard unit is equipped with an integral bypass valve that is built into the closed end cap allowing fluid to flow when the pressure reaches the set level to avoid system shutdown. Elements should be changed to prevent buildup of contaminants in the system. Bypass valve settings are 1-bar, 3-bar and 6-bar.

MEDIA Available	Micron Ratings	Bypass Settings (BPVS) (Options)	
Pleated Microglass Media (also available with water removal media)	3-micron, 5um, 10um, 20um	1-bar 3-bar	
Pleated Paper Media	3-micron, 5um, 10um, 20um		
Stainless Steel Mesh Media (304 SS)	25-micron, 40um, 50um, 74um, 80um, 100um, 149um	6-bar X- No Bypass Valve	

Millennium-Filters are guaranteed to meet or exceed OEM specifications in terms of form, fit and function. OEM part numbers for reference only.

www.Millennium-Filters.com 24855 NOVI ROAD Suite 105 NOVI, MICHIGAN 48375 Phone: 248-719-7441 Fax: 248-869-6090