SF 190-27-P 6" Polycrystalline







Solarfun's photovoltaic modules offer high-powered, reliable performance for solar projects, both on- and off-grid.

The Solarfun Advantage

- 100% of cells are carefully manufactured by Solarfun Power, ensuring excellence at every step of production
- Rugged double-coated aluminum-alloy frame for longevity in adverse conditions
- Every cell is individually inspected and power-matched to ensure consistent performance between the cells in the module array
- Strictly adhering to ISO 9001 quality and ISO 14001 environmental standards









Electrical Characteristics

Maximum Power	P_{max}	170 W	175 W	180 W	185 W	190 W	195 W	200 W	205 W	210 W
Open Circuit Voltage	Voc	32.2 V	32.3 V	32.4 V	32.5 V	32.6 V	32.7 V	32.8 V	32.9 V	33.0 V
Short Circuit Current	Isc	7.54 A	7.64 A	7.72 A	7.80 A	7.98 A	8.06 A	8.24 A	8.35 A	8.48 A
Maximum Power Voltage	V_{mp}	26.3 V	26.4 V	26.5 V	26.6 V	26.7 V	26.8 V	26.9 V	27.0 V	27.1 A
Maximum Power Current	I _{mp}	6.47 A	6.63 A	6.80 A	6.96 A	7.12 A	7.28 A	7.44 A	7.60 A	7.75 A
Module Efficiency (%)		11.4	11.7	12.1	12.4	12.7	13.1	13.4	13.7	14
Tolerance						+/- 5%				


Electrical characteristics at Standard Test Conditions (STC), defined as: Irradiance of 1000W/m2, Spectrum AM 1.5, and Cell temperature of 25°C.

Mechanical Specifications

Dimensions	$1494 \times 1000 \times 45 \text{ mm } [58.8 \times 39.37 \times 1.77 \text{ in}]$					
Weight	18 kg [40 lbs]					
Frame	Aluminium-alloy					
Packing Configuration	36 pcs per pallet					
Size of Pallet	$1.58 \times 1.07 \times 2.14 \text{ m}$ [62.2 × 42.1 × 84.3 in]					
Loading Capacity (40 ft container)	504 pcs					

3 year workmanship and 90/10, 80/25 year power warranty. For full details see the Solarfun Limited Warranty available on request.

Dimensions



© July 2008. Jiangsu Linyang Solarfun. All rights reserved.


Specifications and designs included in this datasheet are subject to change without notice.




Document #: 091-004-071908



IV Curves



Various Temperatures



Various Irradiance Levels

