



## First Team Sports, Inc. | Sport II

- 1. VERTICAL POLE** - Vertical pole shall be one-piece 4" square (sectional posts not considered equal) with a minimum 11 gauge wall thickness and allow for burying 36" in concrete. Posts with thinner wall thickness are not considered equal. Posts intended to be buried less than 36" are not considered equal. Pole shall have a watertight vinyl cap to seal out moisture.
- 2. EXTENSION ARM** - Main 45 degree extension arm tube shall be 2"x3" rectangular 11 gauge wall steel tubing and provide for a 24" extension from front of pole to face of backboard. Extension arm shall be constructed to allow rim bolts to pass through backboard and directly into extension arm for strength and player safety. Extension arm shall be secured to vertical post by means of two 4" zinc plated U-bolts. Additionally, two 1" round backboard braces shall support upper corners of the backboard.
- 3. CONSTRUCTION** - All steel pole components shall be welded using maximum penetration, continuous weld, MIG procedure.
- 4. FINISH** - Pole components shall have a polyester powder-coated black finish.
- 5. BACKBOARD** - Backboard shall be 36"x 48" rectangular acrylic (3/8" thick). Backboard shall be framed with a 1/8" thick anodized aluminum framework. Board shall have bright white 2" boarder and official shooters square screened on the backside to eliminate wear.
- 6. RIM** - Flexible type so as to absorb the stress of player contact. The rim shall be of institutional quality with an official 5/8" diameter ring. Ring opening diameter shall be the standard 18" I.D. Rim shall have an orange powder coated finish. Heavy-duty nylon net shall be provided.
- 7. WARRANTY** - Pole, backboard, and standard rim shall carry a Lifetime Limited Warranty. Entire system weight shall be approximately 145#.