

5800 Transmitters

The 5800 Series of door and window transmitters provide the most reliable, convenient and cost effective solutions for security protection. These devices are powerful and versatile enough to help solve even the toughest, most labor intensive installations.

With a demonstrated outdoor range of over a mile, the 5800 Series has the best performance of any transmitters available today. All 5800 Series transmitters send supervisory messages to the control panel, as well as tamper and low battery notification. The 5800 wireless technology will provide year after year of reliable security.

FEATURES:

5814 Ultra-Small Door/Window Transmitter

Although the 5814's compact design slightly decreases its effective range to maintain a long battery life, it is the perfect solution for difficult to reach places and applications where aesthetics and small size is important (ornate doors/windows, casements, etc.)

- Extremely compact
- Features a built-in reed switch and tamper
- Includes replaceable lithium coin cell battery
- Dimensions: 1-1/2" H x 1-1/5" W x 3/5" D

5815 Door/Window Transmitter

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient, and cost-effective solution for door and window protection.

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Dimensions: 1-1/2" W x 3" H x 7/8" D
- Battery: 3V Lithium

5816 Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR)
- Dimensions: 3-1/16" H x 1-9/16" W x 1-3/16" D



Door/Window Transmitters

5800 Transmitters

SPECIFICATIONS:

5816MN Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches [90° apart] and wired closed circuit contact loop.

- Features a small design for a hidden professional look
- Dimensions: 3-1/16" H x 1-9/16" W x 1-5/32" D

5817 Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports nc open and normally closed applications and fast loop response time. The two auxilia support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5m
- Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D

5817CB Universal Contact-Monitoring Transmitter

The 5817CB is a universal contact-monitoring transmitter that can be used with household and commercial fire and burglary-initiating devices.

- The 5817CB has three unique input loops (zones)
- The first loop (primary loop) is supervised and typically used for high-priority alarm such as commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with magnet
- The third loop is another normally closed household burglary loop. All three loops may be used
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CB
- Dimensions 1-9/16" W x 3-1/2" H x 1-3/16" D

5818 Recessed Transmitter

Contact sensor that provides concealed protection for a door or window.

- Features a tapered cylinder for easy and flush fit
- Includes self-contained transmitter, reed sensor, battery & recessed magnet
- Features a standard white plastic case; brown cases available (5818BR); plastic cover-up plug included
- Use 7/8" drill bit for transmitter
- Use 1/2" drill bit for magnet
- Dimensions:
Transmitter: 13/16" diameter, 4-7/8" long
Magnet: 1/2" diameter, 1-3/4" long

ORDERING:

Part No.	Description
5814	Ultra Small Door/Window Transmitter
5815	Ultra Small Door/Window Transmitter
5816MN	Door/Window Transmitter
5816	Door/Window Transmitter
5817	Three Zone Universal Transmitter
5817CB	Three Zone Universal Transmitter
5818	Recessed Transmitter



165 Eileen Way, Syosset, NY 11791
Copyright ©2002 Pittway Corporation
ADEMCO is an ISO9001 Registered Company

ADEMCO
GROUP