



All Stair Treads and Floor Mats

WWW.ALLPARTITIONS.COM

1.866.255.8645



1.866.255.8640 FAX

R.C. Musson Rubber Stair Treads Specifications

Disc-O-Tred No. 787

DESIGN RUBBER STAIR TREADS

SPECIFICATIONS:

Furnish and install No. 787 Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge; 12-1/2" deep. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep); a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

Grit Strip Disc-O-Tred No. GS787

SPECIFICATIONS:

Furnish and install No. GS787 Grit-Strip Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge, 12-1/2" deep, with two black* 3/4" wide abrasive grit-strips inlaid in tread 1" from front edge, spaced 3/4" apart. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep), a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

Grit Strip Disc-O-Tred No. GS787VI

SPECIFICATIONS:

Furnish and install No. GS787VI Grit-Strip Disc-O-Tred Stair Treads by Musson Rubber Co., Akron, Ohio; 1/4" thick tapering to back edge, 12-1/2" deep, with one black* 2" wide abrasive grit-strip inlaid in tread, 1" from front edge, for access by Visually Impaired. Treads shall have a Flame Spread Rating of 25 or less using ASTM-E-84 Test; an adjustable square nose (1-7/8" deep), a sanded back to assure proper adhesion; contain no asbestos fiber; made of top quality homogenous rubber compound, color extending throughout thickness; free from objectionable odors or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72". Select standard solid color from Color Series III.

Rubber Tread No.622

SPECIFICATIONS:

Furnish and install No. 622 Diamond Design Stair Treads from Musson Rubber, Akron, Ohio; 1/4" thick, tapering to back edge, 12-1/4" deep. Treads shall have a 1-1/2" adjustable square nose (or curved nose); a Flame Spread

Rating of 75 or less using ASTM-E-84 Test; a sanded back to assure proper adhesion; contain no asbestos fiber; molded of top quality homogeneous rubber compound, color extending throughout thickness; free from objectionable odors, blisters, cracks or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I, Color Series II, or Color Series III. (Curved Nose available only in Color Series I.)

Grit Strip Rubber Tread #GS622

SPECIFICATIONS:

Furnish and install No. GS622 Molded Rubber Grit Strip Diamond Design Stair Treads from Musson Rubber Co. 1/4" thick; 12-1/4" deep; with 1-1/2" long adjustable square nose (or curved nose). Two black* 3/4" wide abrasive Grit Strips inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded to top quality homogeneous rubber compound; free of objectionable orders or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I, Color Series II or Color Series III. (Curved Nose available only in Color Series I).

**Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

No. GS 622VI Visually Impaired

SPECIFICATIONS:

Furnish and install No. GS622VI Molded Rubber Visually Impaired Grit-Strip Diamond Design Stair Treads from Musson Rubber Co., 1/4" thick; 12-1/4" deep; with 1-1/2" long adjustable square nose (or curved nose). One black* 2" wide abrasive Grit-Strip inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded of top quality homogenous rubber compound; free of objectionable odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I, Color Series II or Color Series III. (*Curved Nose available only in Color Series I.*)

Rubber Tread No.622

SPECIFICATIONS:

Furnish and install No. 622 Diamond Design Stair Treads from Musson Rubber, Akron, Ohio; 1/4" thick, tapering to back edge, 12-1/4" deep. Treads shall have a 1-1/2" adjustable square nose (or curved nose); a Flame Spread Rating of 75 or less using ASTM-E-84 Test; a sanded back to assure proper adhesion; contain no asbestos fiber; molded of top quality homogeneous rubber compound, color extending throughout thickness; free from objectionable odors, blisters, cracks or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I, Color Series II, or Color Series III. (Curved Nose available only in Color Series I.)

Grit Strip Rubber Tread #GS622

SPECIFICATIONS:

Furnish and install No. GS622 Molded Rubber Grit Strip Diamond Design Stair Treads from Musson Rubber Co. 1/4" thick; 12-1/4" deep; with 1-1/2" long adjustable square nose (or curved nose). Two black* 3/4" wide abrasive Grit Strips inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded to top quality homogeneous rubber compound; free of objectionable orders or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I, Color Series II or Color Series III. (Curved Nose available only in Color Series I).

** Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

No. GS 622VI Visually Impaired

SPECIFICATIONS:

Furnish

and install No. GS622VI Molded Rubber Visually Impaired Grit-Strip Diamond Design Stair Treads from Musson Rubber Co., 1/4" thick; 12-1/4" deep; with 1-1/2" long adjustable square nose (or curved nose). One black* 2" wide abrasive Grit-Strip inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded of top quality homogenous rubber compound; free of objectionable odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I, Color Series II or Color Series III. (Curved Nose available only in Color Series I.).

Rubber Tread No.626

SPECIFICATIONS:

Furnish

and install No. 626 Diamond Design Stair Treads from Musson Rubber, Akron, Ohio; 3/16" thick, tapering to back edge, 12-1/4" deep. Treads shall have a 2" adjustable square nose; a Flame Spread Rating of 75 or less using ASTM-E-84 Test; a sanded back to assure proper adhesion; contain no asbestos fiber; molded of top quality homogeneous rubber compound, color extending throughout thickness; free from objectionable odors, blisters, cracks or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I or Color Series II.

Grit Strip Diamond Design Tread No. GS626

SPECIFICATIONS:

Furnish and install No. GS626 Molded Rubber Grit Strip Diamond Design Stair Treads from Musson Rubber Co. 3/16" thick; 12-1/4" deep; with 2" adjustable square nose. Two black* 3/4" wide abrasive Grit Strips inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded to top quality homogeneous rubber compound; free of objectionable orders or imperfections which might impair service. Select standard length of : 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Series II.

- *Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

No. GS 626VI Visually Impaired

SPECIFICATIONS:

Furnish and install No. GS626VI Molded Rubber Visually Impaired Grit-Strip Diamond Design Stair Treads from Musson Rubber Co., 3/16" thick; 12-1/4" deep; with 2" long adjustable square nose. One Black* 2" wide abrasive Grit-Strip inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded of top quality homogenous rubber compound; free of objectionable odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Series II.

- *Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

Rubber Tread No.626

SPECIFICATIONS:

Furnish and install No. 626 Diamond Design Stair Treads from Musson Rubber, Akron, Ohio; 3/16" thick, tapering to back edge, 12-1/4" deep. Treads shall have a 2" adjustable square nose; a Flame Spread Rating of 75 or less using ASTM-E-84 Test; a sanded back to assure proper adhesion; contain no asbestos fiber; molded of top quality homogeneous rubber compound, color extending throughout thickness; free from objectionable odors, blisters, cracks or imperfections which might impair serviceability. Select standard length of 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I or Color Series II.

Grit Strip Diamond Design Tread No. GS626

SPECIFICATIONS:

Furnish and install No. GS626 Molded Rubber Grit Strip Diamond Design Stair Treads from Musson Rubber Co. 3/16" thick; 12-1/4" deep; with 2" adjustable square nose. Two black* 3/4" wide abrasive Grit Strips inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded to top quality homogeneous rubber compound; free of objectionable orders or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Serie

- *Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

No. GS 626VI Visually Impaired

SPECIFICATIONS:

Furnish and install No. GS626VI Molded Rubber Visually Impaired Grit-Strip Diamond Design Stair Treads from Musson Rubber Co., 3/16" thick; 12-1/4" deep; with 2" long adjustable square nose. One Black* 2" wide abrasive Grit-Strip inlaid in tread, 1" from front edge. Treads shall have a sanded back for proper adhesion; contain no asbestos; molded of top quality homogenous rubber compound; free of objectionable odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Series II.

- *Grit Strip inserts are also available in Brown, Gray, Beige, Safety Yellow or Safety Red at an extra cost.*

Rubber Tread No.750, 700, 725

Smooth Flat Surface

SPECIFICATIONS:

Furnish and install Musson #750 Molded Rubber Smooth Flat Surface Stair Treads, 3/16" thick, tapering to back edge, 12-1/2" deep, with square (or curved) molded nose. Standard sizes: 36", 42", 48", 54", 60" or 72", Select standard color from Color Series I or Color Series II.

No. 700 — HEAVY DUTY

SPECIFICATIONS:

Furnish and install Musson #700 Molded Rubber Smooth Flat Surface Stair Treads 5/16" thick, tapering to back edge, 12-1/2" deep, with square molded nose. Standard sizes: 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I.

No. 725 —Heavy Duty, Long Nose

SPECIFICATIONS:

Furnish and install Musson #725 Molded Rubber Smooth Flat Surface Stair Treads, 5/16" thick, tapering to back edge, 12-1/2" deep with a 1-7/8" long adjustable square nose; to fit pan-filled or molded concrete steps. Standard sizes: 36", 42", 48", 54", 60" or 72"; Select standard color from Color Series I. Adjusta Nose will easily adjust and adhere to steps with return angle nosing between 90° and 60°; allows for good fit on stairways designed for safety or aesthetics.

Grit Strips

Abrasive mineral coated Grit-Strips recessed the length of tread at impact area. Helps prevent slipping. Flat surface Grit-Strip treads offer long wear; easy cleaning; reduce noise. Meets Flame Spread Rating of 75 or less using ASTM-E-84 Test. All treads have a sanded back for better adhesion; contains no asbestos.

Grit Strip No. 250 - Service Weight

Specifications:

Furnish and install #250 Molded Rubber Grit-Strip Stair Treads from Musson Rubber Co., 3/16" thick; 12-1/2" deep; square (or curved) nose. Two Black* 3/4" abrasive Grit-Strips inlaid in tread 1" from front edge. Treads shall be molded of top quality homogenous rubber compound; color throughout thickness; free of odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Series II.

Grit Strip No. 200 - Heavy Duty

Specifications:

Furnish and install #200 Molded Rubber Grit-Strip Stair Treads from Musson Rubber Co., 5/16" thick; 12-1/2" deep; square nose. Two Black* 3/4" abrasive Grit-Strips inlaid in tread, 1" from front edge. Treads shall be molded of top quality homogenous rubber compound; color throughout thickness; free of odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I.

Grit Strip No. 225 - Heavy Duty Long Nose

Specifications:

Furnish and install #225 Molded Rubber Grit-Strip Stair Treads from Musson Rubber Co., 5/16" thick; 12-1/2" deep; 1-7/8" long adjustable square nose. Two Black* abrasive Grit-Strips inlaid in tread, 1" from front edge. Treads shall be molded of top quality homogenous rubber compound; color throughout thickness; free of odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I.

Grit-Strip for Visually Impaired

An abrasive mineral coated Grit-Strip is recessed length of tread at impact area. Meets specs for contrasting color to alert Visually Impaired. Flat surface offers long wear; easy cleaning. Meets Flame Spread Rating of 75 or less using ASTM-E-84 Test. All treads have a sanded back for better adhesion; contains no asbestos.

Grit Strip No. 250VI - Service Weight

Specifications:

Furnish and install #250VI Molded Rubber Visually Impaired Grit-Strip Stair Treads from Musson Rubber Co., 3/16" thick; 12-1/2" deep; square (or curved) nose. One Black* 2" wide abrasive Grit-Strip inlaid in tread 1" from front edge. Treads shall be molded of top quality homogenous rubber compound; color throughout thickness; free of odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I or Color Series II.

Grit Strip No. 200VI - Heavy Duty

Specifications:

Furnish and install #200VI Molded Rubber Visually Impaired Grit-Strip Stair Treads from Musson Rubber Co., 5/16" thick; 12-1/2" deep; square nose. One Black* 2" wide abrasive Grit-Strip inlaid in tread, 1" from front edge. Treads shall be molded of top quality homogenous rubber compound; color throughout thickness; free of odors or imperfections which might impair service. Select standard length of: 36", 42", 48", 54", 60" or 72". Select standard color from Color Series I.

7/17/09