

RULES FOR RAILING NEAR SALTWATER

Below is the list of rules to follow when quoting railing near saltwater. The warranty will be honored if the system is quoted and installed in the following manner. Any changes from the following requirements will void the warranty (ex. 3/16" cable with an anodized system will void the warranty).

ANODIZED ALUMINUM – Within 2 miles

- 1) 2507 1/8" cable and fittings – Field assembly only (3/16" and black oxide cable not an option)
- 2) Anodized posts and top rail (or wood top rail)
- 3) Must include grommet package and plastic domed covers
- 4) Must include 316 grade stainless bolts or lags
- 5) No single post corners (can't use grommets)
- 6) No toggle anchor terminal fittings (can't use grommets)
- 7) Anodizing not available for cover plates, saddle brackets, various link components
- 8) Must include passivation service, rust rescue, and passivation spray

POWDER COATED ALUMINUM – Over 2 miles

- 1) Any 316 grade cable & fittings
- 2) Powder coated posts and any top rail
- 3) Grommets for 1/8" cable
- 4) Standard bolts or lags
- 5) Plastic domed covers or cover plates. Do not need both.
- 6) Passivation spray

2507 SQUARE STAINLESS STEEL – Within 2 miles

- 1) 2507 cable and fittings - 3/16" cable not an option
- 2) 2507 square stainless posts and top rail (or wood top rail)
- 3) 2507 bolts or lags
- 4) Must include passivation service, rust rescue, passivation spray, and Collinite

ELECTRO POLISH ROUND STAINLESS STEEL – Within 2 miles

- 1) 2507 cable and fittings - 3/16" cable not an option
- 2) Electro Polish for round stainless posts and top rail (or wood top rail)
- 3) 2507 bolts or lags
- 4) Must include passivation service, rust rescue, passivation spray, and Collinite

316 STAINLESS STEEL – Over 2 miles

- 1) 316 grade cable & fittings – any size cable (including black oxide)
- 2) 316 grade square or round stainless posts and top rail (or wood top rail)
- 3) Standard bolts or lags
- 4) Passivation spray

CABLE AND FITTINGS ONLY – Within 2 miles

- 1) 2507 cable and fittings – Field Assembly or swageless fittings only - 3/16" cable not an option
- 2) Surface Mount and other cable hardware not an option
- 3) Must include passivation service, rust rescue, and passivation spray